
Subject: Re: [PATCH 1/2] SYSCTL: root unregister routine introduced

Posted by [akpm](#) on Mon, 12 Dec 2011 22:52:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Mon, 12 Dec 2011 21:50:00 +0300

Stanislav Kinsbursky <skinsbursky@parallels.com> wrote:

> This routine is required for SUNRPC sysctl's, which are going to be allocated,
> processed and destroyed per network namespace context.
> IOW, new sysctl root will be registered on network namespace creation and
> thus have to unregister before network namespace destruction.
>

It's a bit suspicious that such a mature subsystem as sysctl newly needs its internals exported like this. Either a) the net namespaces work is doing something which hasn't been done before or b) it is doing something wrong.

So, please explain further so we can confirm that it is a) and not b).

```
> --- a/kernel/sysctl.c
> +++ b/kernel/sysctl.c
> @@ -1701,6 +1701,13 @@ void register_sysctl_root(struct ctl_table_root *root)
>   spin_unlock(&sysctl_lock);
> }
>
> +void unregister_sysctl_root(struct ctl_table_root *root)
> +{
> + spin_lock(&sysctl_lock);
> + list_del(&root->root_list);
> + spin_unlock(&sysctl_lock);
> +}
> +
```

This requires the addition of a declaration to include/linux/sysctl.h.

Once that is done and review is complete, I'd suggest that these two patches be joined into a single patch, and that patch become part of whatever patch series it is which needs them.
