
Subject: [PATCH 00/11] SUNRPC: make sysctl per network namespace context
Posted by [Stanislav Kinsbursky](#) on Wed, 14 Dec 2011 10:45:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

This patch set make SUNRPC sysctl created per network namespace context.
It provides the following functionality:

- 1) Debug sysctl's ({rpc,nfs,nlm,nfsd}_debug) content is modifiable only from init_net network context.
- 2) Write to rpc_debug prints active RPC tasks in sysctl's creator networks context.
- 3) xs tunables are per-net now and modified through per-net sysctl's. IOW, sysctl creator context is used to get tunable during sysctl read/write access (not current one).

The following series consists of:

Stanislav Kinsbursky (11):

- SYSCTL: export root and set handling routines
- SUNRPC: use sysctl path instead of dummy parent table
- SUNRPC: sysctl root for debug table introduced
- SUNRPC: per-net sysctl's set introduced
- SUNRPC: register debug sysctl table per network namespace
- SUNRPC: register xs_tunables sysctl table per network namespace
- SUNRPC: xs tunables per network namespace introduced
- SUNRPC: use per-net xs tunables instead of static ones
- SUNRPC: remove xs_tcp_fin_timeout variable
- SUNRPC: allow debug flags modifications only from init_net
- SUNRPC: sysctl table for rpc_debug introduced

```
include/linux/sunrpc/debug.h | 9 ++
include/linux/sunrpc/sched.h | 1
include/linux/sunrpc/xprtsock.h | 3 +
include/linux/sysctl.h | 1
kernel/sysctl.c | 11 +++
net/sunrpc/netns.h | 12 +++
net/sunrpc/sunrpc_syms.c | 27 ++++++-
net/sunrpc/sysctl.c | 160 ++++++-----
net/sunrpc/xprtrdma/transport.c | 11 ---
net/sunrpc/xprtsock.c | 147 ++++++-----
10 files changed, 293 insertions(+), 89 deletions(-)
```