Subject: Re: [PATCH 0/7] Profiling sleep times (v3)
Posted by Arnaldo Carvalho de M[2] on Tue, 06 Dec 2011 13:45:26 GMT

View Forum Message <> Reply to Message

Em Tue, Dec 06, 2011 at 11:15:07AM +0400, Andrey Vagin escreveu:
> Hello Arnaldo,
>
> I found, that you commit patches for perf. Could you review this part?
>
> Arun Sharma said, that the second versions of patches works ok for him.
> (Arun is the first user of this functionality after me.)

I'm going to check if the patches still apply and then review,

- Arnaldo

> Thanks.
>
> On 11/28/2011 01:03 PM, Andrew Vagin wrote:
> >Do you want to know where your code waits locks for a long time?
> >Yes! It's for you. This feature helps you to find bottlenecks.
> >
> >It's not artificial task. Once one of my colleague was investigating a
> >scalability problem. He pressed sysrq-t some times and tried to merge
> >call-chains by hand. But perf can do that.
> >
> >Problem:
> >The problem is that events sched_stat_* contain call-chains of
> >non-target tasks.
> >About month ago I sent series of patches:
> >
> >[PATCH 0/3] trace: add ability to collect call chains of non current task.
> >
> >Peter and Frederic explained me, that this solve isn't good and will be
> >better to make it in userspace.
> >
> >Now it's in userspace. This series expands "perf inject" to be able to
> >merge sched_switch events and sched_stat* events. sched_switch events
> >contain correct call-chains and sched_stat contains a correct time
> >slices.
> >
> >v2:
> >* Removed all known issues. Now it works completely.
> >* Improved usability of sched-stat scripts according with Arun's comments.
> >v3: fixed accoding to comments from David Ahem
> >
> >Andrew Vagin (7):
> >   perf: use event_name() to get an event name

> >   perf: add ability to record event period
> >   perf: add ability to change event according to sample (v2)
> >   perf: teach "perf inject" to work with files
> >   perf: teach perf inject to merge sched_stat_* and sched_switch events
> >   perf: add scripts for profiling sleep times (v2)
> >   event: add tracepoint for accounting block time
> >
> > include/trace/events/sched.h | 7 ++
> > kernel/sched_fair.c | 2 +
> > tools/perf/builtin-inject.c | 120 +++++++++++++++++++++-
> > tools/perf/builtin-record.c | 5 +
> > tools/perf/scripts/python/bin/sched-stat-record | 65 +++++++++++++
> > tools/perf/scripts/python/bin/sched-stat-report | 5 +
> > tools/perf/util/event.h | 2 +
> > tools/perf/util/evsel.c | 74 +++++++++++++++
> > tools/perf/util/header.c | 2 +-
> > tools/perf/util/session.h | 9 ++
> > 10 files changed, 288 insertions(+), 3 deletions(-)
> > create mode 100644 tools/perf/scripts/python/bin/sched-stat-record
> > create mode 100644 tools/perf/scripts/python/bin/sched-stat-report
> >