
Subject: Re: [PATCH 0/5] NFS: create blocklayout pipe per network namesapce context

Posted by [Myklebust, Trond](#) on Fri, 30 Dec 2011 22:55:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Tue, 2011-11-29 at 13:10 +0300, Stanislav Kinsbursky wrote:

> This patch set was created in context of clone of git
> branch: git://git.linux-nfs.org/projects/trondmy/nfs-2.6.git.
> tag: v3.1
>
> This patch set depends on previous patch sets titled:
> 1) "SUNRPC: initial part of making pipes work in net ns"
> 2) "SUNRPC: cleanup PipeFS for network-namespace-aware users"
> 3) "SUNRPC: make RPC clients use network-namespace-aware PipeFS routines"
> 4) "NFS: create clients and IDMAP pipes per network namespace"
>
> This patch set is the final part of making SUNRPC PipeFS and it's users work in
> network namespace context.
>
> The following series consists of:
>
> ---
>
> Stanislav Kinsbursky (5):
> NFS: handle blocklayout pipe PipeFS dentry by network namespace aware routines
> NFS: blocklayout pipe creation per network namespace context introduced
> NFS: blocklayout PipeFS notifier introduced
> NFS: remove RPC PipeFS mount point reference from blocklayout routines
> SUNRPC: kernel PipeFS mount point creation routines removed
>
>
> fs/nfs/blocklayout/blocklayout.c | 154 ++++++-----
> fs/nfs/blocklayout/blocklayout.h | 3 -
> fs/nfs/blocklayout/blocklayoutdev.c | 5 +
> fs/nfs/blocklayout/blocklayoutdm.c | 7 +-
> fs/nfs/inode.c | 1
> fs/nfs/netns.h | 1
> include/linux/sunrpc/rpc_pipe_fs.h | 2
> net/sunrpc/rpc_pipe.c | 21 ----
> 8 files changed, 137 insertions(+), 57 deletions(-)

These patches need rebasing in order to apply on top of 3.2-rc7...

Cheers
Trond

--

Trond Myklebust
Linux NFS client maintainer

NetApp
Trond.Myklebust@netapp.com
www.netapp.com
