

---

Subject: [PATCH v2 1/4] SUNRPC: use proper network namespace in rpcbind

RPCBPROC\_GETADDR procedure

Posted by [Stanislav Kinsbursky](#) on Fri, 13 Jan 2012 10:02:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Pass request socket network namespace to rpc\_uaddr2sockaddr() instead of hardcoded "init\_net", when decoding address in RPCBPROC\_GETADDR procedure.

Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

---

net/sunrpc/rpcb\_clnt.c | 3 +-+

1 files changed, 2 insertions(+), 1 deletions(-)

diff --git a/net/sunrpc/rpcb\_clnt.c b/net/sunrpc/rpcb\_clnt.c

index 7c6fac0..4ce3a8e 100644

--- a/net/sunrpc/rpcb\_clnt.c

+++ b/net/sunrpc/rpcb\_clnt.c

@@ -934,7 +934,8 @@ static int rpcb\_dec\_getaddr(struct rpc\_rqst \*req, struct xdr\_stream \*xdr,  
dprintk("RPC: %5u RPCB\_%s reply: %s\n", task->tk\_pid,  
task->tk\_msg.rpc\_proc->p\_name, (char \*)p);

- if (rpc\_uaddr2sockaddr(&init\_net, (char \*)p, len, sap, sizeof(address)) == 0)

+ if (rpc\_uaddr2sockaddr(req->rq\_xprt->xprt\_net, (char \*)p, len,

+ sap, sizeof(address)) == 0)

goto out\_fail;

rpcb->r\_port = rpc\_get\_port(sap);

---