
Subject: Re: [PATCH 3/5] SUNRPC: create GSS auth cache per network namespace

Posted by [Stanislav Kinsbursky](#) on Thu, 19 Jan 2012 17:04:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

> On Thu, Jan 19, 2012 at 06:49:23PM +0400, Stanislav Kinsbursky wrote:

>> @@ -1000,6 +996,7 @@ static int svcauth_gss_handle_init(struct svc_rqst *rqstp,

>> struct xdr_netobj tmpobj;

>> struct rsi *rsip, rsikey;

>> int ret;

>> + struct sunrpc_net *sn = net_generic(rqstp->rq_xprt->xpt_net, sunrpc_net_id);

>

> OK, so you're getting the network namespace out of the rqstp, and, then

> passing it down, makes sense. And:

>

>> @@ -1079,6 +1076,7 @@ svcauth_gss_accept(struct svc_rqst *rqstp, __be32 *authp)

>> __be32 *rpcstart;

>> __be32 *reject_stat = resv->iiov_base + resv->iiov_len;

>> int ret;

>> + struct sunrpc_net *sn = net_generic(rqstp->rq_xprt->xpt_net, sunrpc_net_id);

>

> ... same for the gss cache. Looks good.

>

> How do you plan to test this?

>

Do you mean something special or in general?

Currently I validate all my changes in container by using simple test environment.

I would be appreciate for any hints to tests, than can help.

--

Best regards,
Stanislav Kinsbursky
