
Subject: [PATCH] NFS: remove unused nfs4_find_client_no_ident function

Posted by [Stanislav Kinsbursky](#) on Fri, 20 Jan 2012 13:19:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

Looks like this function survived after some cleanup patch without a reason.
Now it's not called or referenced and I believe, that it can be simply removed.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfs/client.c | 27 -----

fs/nfs/internal.h | 1 -

2 files changed, 0 insertions(+), 28 deletions(-)

diff --git a/fs/nfs/client.c b/fs/nfs/client.c

index df60d99..34c8d1c 100644

--- a/fs/nfs/client.c

+++ b/fs/nfs/client.c

@@ -1199,33 +1199,6 @@ error:

/*

* NFSv4.0 callback thread helper

*

- * Find a client by IP address, protocol version, and minorversion

- *

- * Called from the pg_authenticate method. The callback identifier

- * is not used as it has not been decoded.

- *

- * Returns NULL if no such client

- */

-struct nfs_client *

-nfs4_find_client_no_ident(const struct sockaddr *addr)

#{

- struct nfs_client *clp;

-

- spin_lock(&nfs_client_lock);

- list_for_each_entry(clp, &nfs_client_list, cl_share_link) {

- if (nfs4_cb_match_client(addr, clp, 0) == false)

- continue;

- atomic_inc(&clp->cl_count);

- spin_unlock(&nfs_client_lock);

- return clp;

- }

- spin_unlock(&nfs_client_lock);

- return NULL;

-}

-

/*

- * NFSv4.0 callback thread helper

```
_ *
* Find a client by callback identifier
*/
struct nfs_client *
diff --git a/fs/nfs/internal.h b/fs/nfs/internal.h
index 2b9836f..eda4cde4 100644
--- a/fs/nfs/internal.h
+++ b/fs/nfs/internal.h
@@ -149,7 +149,6 @@ extern struct rpc_program nfs_program;

extern void nfs_cleanup_cb_ident_idr(void);
extern void nfs_put_client(struct nfs_client *);
-extern struct nfs_client *nfs4_find_client_no_ident(const struct sockaddr *);
extern struct nfs_client *nfs4_find_client_ident(int);
extern struct nfs_client *
nfs4_find_client_sessionid(const struct sockaddr *, struct nfs4_sessionid *);
```
