

---

Subject: [PATCH] NFS: remove unused nfs4\_find\_client\_no\_ident function

Posted by Stanislav Kinsbursky on Fri, 20 Jan 2012 13:19:56 GMT

[View Forum Message](#) <[Reply to Message](#)

---

Looks like this function survived after some cleanup patch without a reason.  
Now it's not called or referenced and I believe, that it can be simply removed.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

---

```
fs/nfs/client.c | 27 -----
fs/nfs/internal.h | 1 -
2 files changed, 0 insertions(+), 28 deletions(-)
```

```
diff --git a/fs/nfs/client.c b/fs/nfs/client.c
index df60d99..34c8d1c 100644
--- a/fs/nfs/client.c
+++ b/fs/nfs/client.c
@@ -1199,33 +1199,6 @@ error:
/*
 * NFSv4.0 callback thread helper
 *
- * Find a client by IP address, protocol version, and minorversion
- *
- * Called from the pg_authenticate method. The callback identifier
- * is not used as it has not been decoded.
- *
- * Returns NULL if no such client
- */
-struct nfs_client *
-nfs4_find_client_no_ident(const struct sockaddr *addr)
-{
- struct nfs_client *clp;
-
- spin_lock(&nfs_client_lock);
- list_for_each_entry(clp, &nfs_client_list, cl_share_link) {
- if (nfs4_cb_match_client(addr, clp, 0) == false)
- continue;
- atomic_inc(&clp->cl_count);
- spin_unlock(&nfs_client_lock);
- return clp;
- }
- spin_unlock(&nfs_client_lock);
- return NULL;
-}
-
-/*
- * NFSv4.0 callback thread helper
```

```
- *
 * Find a client by callback identifier
 */
struct nfs_client *
diff --git a/fs/nfs/internal.h b/fs/nfs/internal.h
index 2b9836f..eda4cde4 100644
--- a/fs/nfs/internal.h
+++ b/fs/nfs/internal.h
@@ -149,7 +149,6 @@ extern struct rpc_program nfs_program;

extern void nfs_cleanup_cb_ident_idr(void);
extern void nfs_put_client(struct nfs_client *);
-extern struct nfs_client *nfs4_find_client_no_ident(const struct sockaddr *);
extern struct nfs_client *nfs4_find_client_ident(int);
extern struct nfs_client *
nfs4_find_client_sessionid(const struct sockaddr *, struct nfs4_sessionid *);
```

---