
Subject: [PATCH 4/5] NFS: pass current net to rpc_pton() while parsing mount options

Posted by Stanislav Kinsbursky on Thu, 26 Jan 2012 11:11:57 GMT

[View Forum Message](#) <[Reply to Message](#)

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfs/super.c | 4 +---
1 files changed, 2 insertions(+), 2 deletions(-)

```
diff --git a/fs/nfs/super.c b/fs/nfs/super.c
index b79f2a1..5ed6071 100644
--- a/fs/nfs/super.c
+++ b/fs/nfs/super.c
@@ -1408,7 +1408,7 @@ static int nfs_parse_mount_options(char *raw,
    if (string == NULL)
        goto out_nomem;
    mnt->nfs_server.addrlen =
-    rpc_pton(&init_net, string, strlen(string)),
+    rpc_pton(mnt->net, string, strlen(string),
              (struct sockaddr *)
              &mnt->nfs_server.address,
              sizeof(mnt->nfs_server.address));
@@ -1430,7 +1430,7 @@ static int nfs_parse_mount_options(char *raw,
    if (string == NULL)
        goto out_nomem;
    mnt->mount_server.addrlen =
-    rpc_pton(&init_net, string, strlen(string)),
+    rpc_pton(mnt->net, string, strlen(string),
              (struct sockaddr *)
              &mnt->mount_server.address,
              sizeof(mnt->mount_server.address));
```
