
Subject: [PATCH 4/5] NFS: pass current net to rpc_pton() while parsing mount options

Posted by [Stanislav Kinsbursky](#) on Thu, 26 Jan 2012 11:11:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfs/super.c | 4 ++--

1 files changed, 2 insertions(+), 2 deletions(-)

diff --git a/fs/nfs/super.c b/fs/nfs/super.c

index b79f2a1..5ed6071 100644

--- a/fs/nfs/super.c

+++ b/fs/nfs/super.c

@@ -1408,7 +1408,7 @@ static int nfs_parse_mount_options(char *raw,

if (string == NULL)

goto out_nomem;

mnt->nfs_server.addrlen =

- rpc_pton(&init_net, string, strlen(string),

+ rpc_pton(mnt->net, string, strlen(string),

(struct sockaddr *)

&mnt->nfs_server.address,

sizeof(mnt->nfs_server.address));

@@ -1430,7 +1430,7 @@ static int nfs_parse_mount_options(char *raw,

if (string == NULL)

goto out_nomem;

mnt->mount_server.addrlen =

- rpc_pton(&init_net, string, strlen(string),

+ rpc_pton(mnt->net, string, strlen(string),

(struct sockaddr *)

&mnt->mount_server.address,

sizeof(mnt->mount_server.address));
