
Subject: [PATCH 5/5] NFS: pass transport net to rpc_pton() while parse server name

Posted by [Stanislav Kinsbursky](#) on Thu, 26 Jan 2012 11:12:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfs/nfs4namespace.c | 6 +++---

1 files changed, 3 insertions(+), 3 deletions(-)

diff --git a/fs/nfs/nfs4namespace.c b/fs/nfs/nfs4namespace.c

index 48a9acd..667ea74 100644

--- a/fs/nfs/nfs4namespace.c

+++ b/fs/nfs/nfs4namespace.c

@@ -97,11 +97,11 @@ static size_t nfs_parse_server_name(char *string, size_t len,
struct sockaddr *sa, size_t salen, struct nfs_server *server)

{

ssize_t ret;

+ struct net *net = server->client->cl_xprt->xprt_net;

- ret = rpc_pton(&init_net, string, len, sa, salen);

+ ret = rpc_pton(net, string, len, sa, salen);

if (ret == 0) {

- ret = nfs_dns_resolve_name(server->client->cl_xprt->xprt_net,

- string, len, sa, salen);

+ ret = nfs_dns_resolve_name(net, string, len, sa, salen);

if (ret < 0)

ret = 0;

}
