
Subject: [PATCH 1/5] make steal time's to-tick routine generic
Posted by [Glauber Costa](#) on Thu, 02 Feb 2012 14:19:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

In this patchset, I am exposing other data as ticks as well, that are originally nanoseconds. Whether or not I should do it, it is open for debate, and I am happy to drop this patch if we decide not to. But right now this exists to support the further patch that uses it.

Signed-off-by: Glauber Costa <glommer@parallels.com>

kernel/sched/core.c | 13 ++++++++----
1 files changed, 9 insertions(+), 4 deletions(-)

diff --git a/kernel/sched/core.c b/kernel/sched/core.c

index b9be4ba..455810f 100644

--- a/kernel/sched/core.c

+++ b/kernel/sched/core.c

@@ -850,13 +850,18 @@ EXPORT_SYMBOL_GPL(account_system_vtime);

#endif /* CONFIG_IRQ_TIME_ACCOUNTING */

```
+static inline u64 nsec_to_tick(u64 nsec)
+{
+ if (unlikely(nsec > NSEC_PER_SEC))
+ return div_u64(nsec, TICK_NSEC);
+
+ return __iter_div_u64_rem(nsec, TICK_NSEC, &nsec);
+}
+
+#ifdef CONFIG_PARAVIRT
static inline u64 steal_ticks(u64 steal)
{
- if (unlikely(steal > NSEC_PER_SEC))
- return div_u64(steal, TICK_NSEC);
-
- return __iter_div_u64_rem(steal, TICK_NSEC, &steal);
+ return nsec_to_tick(steal);
}
#endif
```

--

1.7.7.4
