

---

Subject: Re: [PATCH 1/4] NFS: make nfs\_client\_list per net ns  
Posted by [Myklebust, Trond](#) on Tue, 07 Feb 2012 15:34:48 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

On Tue, 2012-02-07 at 10:32 -0500, Bryan Schumaker wrote:

> I fixed up my bisect and identified this patch instead. The problem I'm seeing is:

```
>
> CC [M] fs/nfs/delegation.o
> CC [M] fs/nfs/idmap.o
> fs/nfs/idmap.c: In function 'rpc_pipefs_event':
> fs/nfs/idmap.c:535:9: error: implicit declaration of function 'net_generic'
> [-Werror=implicit-function-declaration]
> fs/nfs/idmap.c:535:50: error: 'nfs_net_id' undeclared (first use in this function)
> fs/nfs/idmap.c:535:50: note: each undeclared identifier is reported only once for each function it
appears in
> fs/nfs/idmap.c:540:82: error: dereferencing pointer to incomplete type
> fs/nfs/idmap.c:540:224: error: dereferencing pointer to incomplete type
> cc1: some warnings being treated as errors
>
> make[2]: *** [fs/nfs/idmap.o] Error 1
> make[1]: *** [fs/nfs] Error 2
> make: *** [fs] Error 2
>
> I think you need to add: #include "netns.h" to idmap.c.
>
> - Bryan
```

That should already be there in the 'devel' branch. See commit  
17347d03c008e2f504c33bb4905cdad0abc01319.

--  
Trond Myklebust  
Linux NFS client maintainer

NetApp  
Trond.Myklebust@netapp.com  
www.netapp.com

---