

Subject: Re: [PATCH] SUNRPC: set desired file system root before connecting local transports

Posted by [Myklebust, Trond](#) on Wed, 07 Mar 2012 00:21:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wed, 2012-03-07 at 00:19 +0000, Myklebust, Trond wrote:

> On Wed, 2012-02-29 at 18:59 +0400, Stanislav Kinsbursky wrote:

> > Today, there is a problem in connecting of local SUNRPC transports. These
> > transports uses UNIX sockets and connection itself is done by rpciod workqueue.

> > But UNIX sockets lookup is done in context of process file system root. I.e.

> > all local transports are connecting in rpciod context.

> > This works nice until we will try to mount NFS from process with other root -

> > for example in container. This container can have it's own (nested) root and

> > rpcbind process, listening on it's own unix sockets. But NFS mount attempt in

> > this container will register new service (Lockd for example) in global rpcbind

> > - not containers's one.

> > This patch solves the problem by switching rpciod kernel thread's file system

> > root to right one (stored on transport) while connecting of local transports.

> >

> > Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

> >

> > ---

> > fs/fs_struct.c | 1 +

> > net/sunrpc/xprtsock.c | 32 ++++++++-----

> > 2 files changed, 31 insertions(+), 2 deletions(-)

> >

> > diff --git a/fs/fs_struct.c b/fs/fs_struct.c

> > index 78b519c..0f984c3 100644

> > --- a/fs/fs_struct.c

> > +++ b/fs/fs_struct.c

> > @@ -36,6 +36,7 @@ void set_fs_root(struct fs_struct *fs, struct path *path)

> > if (old_root.dentry)

> > path_put_longterm(&old_root);

> > }

> > +EXPORT_SYMBOL_GPL(set_fs_root);

> >

> > /*

> > * Replace the fs->{pwmnt,pwd} with {mnt,dentry}. Put the old values.

> > diff --git a/net/sunrpc/xprtsock.c b/net/sunrpc/xprtsock.c

> > index 4c8281d..c94c181 100644

> > --- a/net/sunrpc/xprtsock.c

> > +++ b/net/sunrpc/xprtsock.c

> > @@ -37,6 +37,7 @@

> > #include <linux/sunrpc/svcsock.h>

> > #include <linux/sunrpc/xprtsock.h>

> > #include <linux/file.h>

> > + #include <linux/fs_struct.h>

> > #ifdef CONFIG_SUNRPC_BACKCHANNEL

```

>> #include <linux/sunrpc/bc_xprt.h>
>> #endif
>> @@ -255,6 +256,11 @@ struct sock_xprt {
>> void (*old_state_change)(struct sock *);
>> void (*old_write_space)(struct sock *);
>> void (*old_error_report)(struct sock *);
>> +
>> + /*
>> + * Saved transport creator root. Required for local transports only.
>> + */
>> + struct path root;
>> };
>>
>> /*
>> @@ -1891,6 +1897,7 @@ static void xs_local_setup_socket(struct work_struct *work)
>> struct rpc_xprt *xprt = &transport->xprt;
>> struct socket *sock;
>> int status = -EIO;
>> + struct path root;
>>
>> if (xprt->shutdown)
>> goto out;
>> @@ -1908,7 +1915,14 @@ static void xs_local_setup_socket(struct work_struct *work)
>> dprintk("RPC: worker connecting xprt %p via AF_LOCAL to %s\n",
>> xprt, xprt->address_strings[RPC_DISPLAY_ADDR]);
>>
>> + get_fs_root(current->fs, &root);
>> + set_fs_root(current->fs, &transport->root);
>> +
>> status = xs_local_finish_connecting(xprt, sock);
>> +
>> + set_fs_root(current->fs, &root);
>> + path_put(&root);
>> +
>> switch (status) {
>> case 0:
>
> Hi Stanislav,
>
> What happens here if the mount namespace of the process that originally
> created the sock_xprt no longer exists? Should we care about that case?
>
> Cheers
> Trond

```

BTW: We will in any case need Al Viro and Christoph's ACK in order to export the set_fs_root() function.

--

Trond Myklebust
Linux NFS client maintainer

NetApp
Trond.Myklebust@netapp.com
www.netapp.com
