
Subject: Re: [PATCH 3/4] provide a function to register more cftype files into memcg

Posted by [Tejun Heo](#) on Tue, 20 Mar 2012 18:32:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hey,

On Tue, Mar 20, 2012 at 08:50:55PM +0400, Glauber Costa wrote:

> The function mem_cgroup_register_cftype() is provided here, so
> an optional memcg subsystem that needs to register files at
> a time later than memcg initialization can do it.

>

> Signed-off-by: Glauber Costa <glommer@parallels.com>

> CC: Tejun Heo <tj@kernel.org>

> CC: Aneesh Kumar K.V <aneesh.kumar@linux.vnet.ibm.com>

> ---

> include/linux/memcontrol.h | 1 +

> mm/memcontrol.c | 6 ++++++

> 2 files changed, 7 insertions(+), 0 deletions(-)

>

> diff --git a/include/linux/memcontrol.h b/include/linux/memcontrol.h

> index 4d34356..bcf8de3 100644

> --- a/include/linux/memcontrol.h

> +++ b/include/linux/memcontrol.h

> @@ -141,6 +141,7 @@ static inline bool mem_cgroup_disabled(void)

> return false;

> }

>

> +int mem_cgroup_register_cftype(const struct cftype *cfts);

> void mem_cgroup_update_page_stat(struct page *page,

> enum mem_cgroup_page_stat_item idx,

> int val);

> diff --git a/mm/memcontrol.c b/mm/memcontrol.c

> index f7c6727..bd91a46 100644

> --- a/mm/memcontrol.c

> +++ b/mm/memcontrol.c

> @@ -444,6 +444,12 @@ struct cgroup_subsys_state *mem_cgroup_css(struct mem_cgroup *memcg)

> return &memcg->css;

> }

>

> +int mem_cgroup_register_cftype(const struct cftype *cfts)

> +{

> + return WARN_ON(cgroup_add_cftypes(&mem_cgroup_subsys, cfts));

> +}

> +EXPORT_SYMBOL(mem_cgroup_register_cftype);

Why not just export mem_cgroup_subsys?

Thanks.

--
tejun
