
Subject: [PATCH 4/8] nfsd: use exp_put() for svc_export_cache put
Posted by [Stanislav Kinsbursky](#) on Wed, 28 Mar 2012 15:09:22 GMT
[View Forum Message](#) <> [Reply to Message](#)

This patch replaces cache_put() call for svc_export_cache by exp_put() call.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfsd/export.c | 2 +-
fs/nfsd/nfsfh.c | 2 +-
2 files changed, 2 insertions(+), 2 deletions(-)

```
diff --git a/fs/nfsd/export.c b/fs/nfsd/export.c
index 99ea4c0..c20a405 100644
--- a/fs/nfsd/export.c
+++ b/fs/nfsd/export.c
@@ -1205,7 +1205,7 @@ static int e_show(struct seq_file *m, void *p)
     cache_get(&exp->h);
     if (cache_check(&svc_export_cache, &exp->h, NULL))
         return 0;
-    cache_put(&exp->h, &svc_export_cache);
+    exp_put(exp);
     return svc_export_show(m, &svc_export_cache, cp);
 }
```

```
diff --git a/fs/nfsd/nfsfh.c b/fs/nfsd/nfsfh.c
index 68454e7..cc79300 100644
--- a/fs/nfsd/nfsfh.c
+++ b/fs/nfsd/nfsfh.c
@@ -636,7 +636,7 @@ fh_put(struct svc_fh *fhp)
 #endif
 }
 if (exp) {
-    cache_put(&exp->h, &svc_export_cache);
+    exp_put(exp);
     fhp->fh_export = NULL;
 }
 return;
```
