
Subject: [PATCH 03/10] NFS: move per-net callback thread initialization to
nfs_callback_up_net()

Posted by [Stanislav Kinsbursky](#) on Thu, 26 Apr 2012 15:55:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

This new function is now called before nfs_minorversion_callback_svc_setup()).

Also few small changes:

- 1) current network namespace in nfs_callback_up() was replaced by transport net.
- 2) svc_shutdown_net() was moved prior to callback usage counter decrement (because in case of per-net data allocation failure svc_shutdown_net() have to be skipped).

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfs/callback.c | 125 ++++++-----
1 files changed, 78 insertions(+), 47 deletions(-)

diff --git a/fs/nfs/callback.c b/fs/nfs/callback.c

index 786f21c..9f5e790 100644

--- a/fs/nfs/callback.c

+++ b/fs/nfs/callback.c

@@ -64,6 +64,32 @@ static struct kernel_param_ops param_ops_portnr = {

module_param_named(callback_tcpport, nfs_callback_set_tcpport, portnr, 0644);

+static int nfs4_callback_up_net(struct svc_serv *serv, struct net *net)

+{

+ int ret;

+

+ ret = svc_create_xprt(serv, "tcp", net, PF_INET,

+ nfs_callback_set_tcpport, SVC_SOCKET_ANONYMOUS);

+ if (ret <= 0)

+ goto out_err;

+ nfs_callback_tcpport = ret;

+ dprintk("NFS: Callback listener port = %u (af %u, net %p)\n",

+ nfs_callback_tcpport, PF_INET, net);

+

+ ret = svc_create_xprt(serv, "tcp", net, PF_INET6,

+ nfs_callback_set_tcpport, SVC_SOCKET_ANONYMOUS);

+ if (ret > 0) {

+ nfs_callback_tcpport6 = ret;

+ dprintk("NFS: Callback listener port = %u (af %u, net %p)\n",

+ nfs_callback_tcpport6, PF_INET6, net);

+ } else if (ret != -EAFNOSUPPORT)

+ goto out_err;

+ return 0;

```

+
+out_err:
+ return (ret) ? ret : -ENOMEM;
+}
+
+/*
+ * This is the NFSv4 callback kernel thread.
+ */
@@ -105,36 +131,21 @@ nfs4_callback_svc(void *vrqstp)
static struct svc_rqst *
nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
{
- int ret;
-
- ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET,
-   nfs_callback_set_tcpport, SVC_SOCKET_ANONYMOUS);
- if (ret <= 0)
-   goto out_err;
- nfs_callback_tcpport = ret;
- dprintk("NFS: Callback listener port = %u (af %u)\n",
-   nfs_callback_tcpport, PF_INET);
-
- ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET6,
-   nfs_callback_set_tcpport, SVC_SOCKET_ANONYMOUS);
- if (ret > 0) {
-   nfs_callback_tcpport6 = ret;
-   dprintk("NFS: Callback listener port = %u (af %u)\n",
-     nfs_callback_tcpport6, PF_INET6);
- } else if (ret == -EAFNOSUPPORT)
-   ret = 0;
- else
-   goto out_err;
-
-   return svc_prepare_thread(serv, &serv->sv_pools[0], NUMA_NO_NODE);
-
-out_err:
- if (ret == 0)
-   ret = -ENOMEM;
- return ERR_PTR(ret);
}

#ifdef CONFIG_NFS_V4_1
+static int nfs41_callback_up_net(struct svc_serv *serv, struct net *net)
+{
+ /*
+  * Create an svc_sock for the back channel service that shares the
+  * fore channel connection.
+  * Returns the input port (0) and sets the svc_serv bc_xprt on success

```

```

+ */
+ return svc_create_xprt(serv, "tcp-bc", net, PF_INET, 0,
+     SVC_SOCKET_ANONYMOUS);
+}
+
/*
 * The callback service for NFSv4.1 callbacks
 */
@@ -177,19 +188,6 @@ static struct svc_rqst *
nfs41_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
{
    struct svc_rqst *rqstp;
- int ret;
-
- /*
-  * Create an svc_sock for the back channel service that shares the
-  * fore channel connection.
-  * Returns the input port (0) and sets the svc_serv bc_xprt on success
-  */
- ret = svc_create_xprt(serv, "tcp-bc", xprt->xprt_net, PF_INET, 0,
-     SVC_SOCKET_ANONYMOUS);
- if (ret < 0) {
-     rqstp = ERR_PTR(ret);
-     goto out;
- }

    /*
     * Save the svc_serv in the transport so that it can
@@ -205,7 +203,6 @@ nfs41_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
    svc_xprt_put(serv->sv_bc_xprt);
    serv->sv_bc_xprt = NULL;
}
-out:
    dprintk("--> %s return %ld\n", __func__,
        IS_ERR(rqstp) ? PTR_ERR(rqstp) : 0);
    return rqstp;
@@ -229,6 +226,11 @@ static inline void nfs_callback_bc_serv(u32 minorversion, struct rpc_xprt
*xprt,
    xprt->bc_serv = cb_info->serv;
}
#else
+static int nfs41_callback_up_net(struct svc_serv *serv, struct net *net)
+{
+    return 0;
+}
+
static inline int nfs_minorversion_callback_svc_setup(u32 minorversion,
    struct svc_serv *serv, struct rpc_xprt *xprt,

```

```

    struct svc_rqst **rqstpp, int (**callback_svc)(void *vrqstp))
@@ -242,6 +244,36 @@ static inline void nfs_callback_bc_serv(u32 minorversion, struct rpc_xprt
*xprt,
}
#endif /* CONFIG_NFS_V4_1 */

+static int nfs_callback_up_net(int minorversion, struct svc_serv *serv, struct net *net)
+{
+ int ret;
+
+ dprintk("NFS: create per-net callback data; net=%p\n", net);
+
+ ret = svc_bind(serv, net);
+ if (ret < 0) {
+ printk(KERN_WARNING "NFS: bind callback service failed\n");
+ goto err_bind;
+ }
+
+ if (minorversion) {
+ ret = nfs41_callback_up_net(serv, net);
+ if (ret < 0)
+ goto err_socks;
+ }
+
+ if (ret == 0)
+ ret = nfs4_callback_up_net(serv, net);
+ if (ret < 0)
+ goto err_socks;
+ return 0;
+
+err_socks:
+ svc_rpcb_cleanup(serv, net);
+err_bind:
+ return ret;
+}
+
static struct svc_serv *nfs_callback_create_svc(int minorversion)
{
    struct nfs_callback_data *cb_info = &nfs_callback_info[minorversion];
@@ -288,7 +320,7 @@ int nfs_callback_up(u32 minorversion, struct rpc_xprt *xprt)
    char svc_name[12];
    int ret = 0;
    int minorversion_setup;
- struct net *net = current->nsproxy->net_ns;
+ struct net *net = xprt->xprt_net;

    mutex_lock(&nfs_callback_mutex);

```

```

@@ -303,11 +335,9 @@ int nfs_callback_up(u32 minorversion, struct rpc_xprt *xprt)
    goto out;
}

- ret = svc_bind(serv, net);
- if (ret < 0) {
-   printk(KERN_WARNING "NFS: bind callback service failed\n");
-   goto out_err;
- }
+ ret = nfs_callback_up_net(minorversion, serv, net);
+ if (ret < 0)
+   goto err_net;

    minorversion_setup = nfs_minorversion_callback_svc_setup(minorversion,
        serv, xprt, &rqstp, &callback_svc);
@@ -347,10 +377,11 @@ err_create:
    mutex_unlock(&nfs_callback_mutex);
    return ret;
out_err:
+ svc_shutdown_net(serv, net);
+err_net:
    dprintk("NFS: Couldn't create callback socket or server thread; "
        "err = %d\n", ret);
    cb_info->users--;
-   svc_shutdown_net(serv, net);
    goto out;
}

```
