
Subject: Re: [PATCH v7 1/2] Always free struct memcg through schedule_work()
Posted by [Michal Hocko](#) on Fri, 25 May 2012 09:50:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Fri 25-05-12 13:32:07, Glauber Costa wrote:

> Right now we free struct memcg with kfree right after a
> rcu grace period, but defer it if we need to use vfree() to get
> rid of that memory area. We do that by need, because we need vfree
> to be called in a process context.
>
> This patch unifies this behavior, by ensuring that even kfree will
> happen in a separate thread. The goal is to have a stable place to
> call the upcoming jump label destruction function outside the realm
> of the complicated and quite far-reaching cgroup lock (that can't be
> held when calling neither the cpu_hotplug.lock nor the jump_label_mutex)
>
> Signed-off-by: Glauber Costa <glommer@parallels.com>
> Acked-by: Kamezawa Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

Acked-by: Michal Hocko <mhocko@suse.cz>

Just one comment below

> CC: Tejun Heo <tj@kernel.org>
> CC: Li Zefan <lizefan@huawei.com>
> CC: Johannes Weiner <hannes@cmpxchg.org>
> CC: Michal Hocko <mhocko@suse.cz>
> CC: Andrew Morton <akpm@linux-foundation.org>
> ---
> mm/memcontrol.c | 24 ++++++++-----
> 1 files changed, 13 insertions(+), 11 deletions(-)
>
> diff --git a/mm/memcontrol.c b/mm/memcontrol.c
> index 932a734..0b4b4c8 100644
> --- a/mm/memcontrol.c
> +++ b/mm/memcontrol.c
> [...]
> @@ -4826,23 +4826,28 @@ out_free:
> }
>
> /*
> - * Helpers for freeing a vzalloc()ed mem_cgroup by RCU,
> + * Helpers for freeing a kmalloc()ed/vzalloc()ed mem_cgroup by RCU,
> * but in process context. The work_freeing structure is overlaid
> * on the rcu_freeing structure, which itself is overlaid on memsw.
> */
> -static void vfree_work(struct work_struct *work)
> +static void free_work(struct work_struct *work)

```
> {  
> struct mem_cgroup *memcg;  
> + int size = sizeof(struct mem_cgroup);  
>  
> memcg = container_of(work, struct mem_cgroup, work_freeing);  
> - vfree(memcg);  
> + if (size < PAGE_SIZE)
```

What about

```
if (is_vmalloc_addr(memcg))  
> + kfree(memcg);  
> + else  
> + vfree(memcg);  
> }
```

--

Michal Hocko
SUSE Labs
SUSE LINUX s.r.o.
Lihovarska 1060/12
190 00 Praha 9
Czech Republic
