
Subject: [PATCH v3 18/28] slub: charge allocation to a memcg
Posted by [Glauber Costa](#) on Fri, 25 May 2012 13:03:38 GMT
[View Forum Message](#) <> [Reply to Message](#)

This patch charges allocation of a slab object to a particular memcg.

The cache is selected with `mem_cgroup_get_kmem_cache()`, which is the biggest overhead we pay here, because it happens at all allocations. However, other than forcing a function call, this function is not very expensive, and try to return as soon as we realize we are not a memcg cache.

The charge/uncharge functions are heavier, but are only called for new page allocations.

The `kmalloc_no_account` variant is patched so the base function is used and we don't even try to do cache selection.

Signed-off-by: Glauber Costa <glommer@parallels.com>
CC: Christoph Lameter <cl@linux.com>
CC: Pekka Enberg <penberg@cs.helsinki.fi>
CC: Michal Hocko <mhocko@suse.cz>
CC: Kamezawa Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>
CC: Johannes Weiner <hannes@cmpxchg.org>
CC: Suleiman Souhlal <suleiman@google.com>

```
include/linux/slub_def.h | 39 ++++++++  
mm/slub.c                | 87 ++++++++  
2 files changed, 112 insertions(+), 14 deletions(-)
```

```
diff --git a/include/linux/slub_def.h b/include/linux/slub_def.h  
index f822ca2..ba9c68b 100644
```

```
--- a/include/linux/slub_def.h  
+++ b/include/linux/slub_def.h
```

```
@@ -13,6 +13,8 @@  
#include <linux/kobject.h>
```

```
#include <linux/kmemleak.h>  
+#include <linux/memcontrol.h>  
+#include <linux/mm.h>
```

```
enum stat_item {  
    ALLOC_FASTPATH, /* Allocation from cpu slab */  
@@ -228,27 +230,54 @@ static __always_inline int kmalloc_index(size_t size)  
    * This ought to end up with a global pointer to the right cache  
    * in kmalloc_caches.
```

```

*/
-static __always_inline struct kmem_cache *kmalloc_slab(size_t size)
+static __always_inline struct kmem_cache *kmalloc_slab(gfp_t flags, size_t size)
{
+ struct kmem_cache *s;
  int index = kmalloc_index(size);

  if (index == 0)
    return NULL;

- return kmalloc_caches[index];
+ s = kmalloc_caches[index];
+
+ rcu_read_lock();
+ s = mem_cgroup_get_kmem_cache(s, flags);
+ rcu_read_unlock();
+
+ return s;
}

void *kmem_cache_alloc(struct kmem_cache *, gfp_t);
void *__kmalloc(size_t size, gfp_t flags);

static __always_inline void *
-kmalloc_order(size_t size, gfp_t flags, unsigned int order)
+kmalloc_order_base(size_t size, gfp_t flags, unsigned int order)
{
  void *ret = (void *) __get_free_pages(flags | __GFP_COMP, order);
  kmemleak_alloc(ret, size, 1, flags);
  return ret;
}

+static __always_inline void *
+kmalloc_order(size_t size, gfp_t flags, unsigned int order)
+{
+ void *ret = NULL;
+ struct page *page;
+
+ ret = kmalloc_order_base(size, flags, order);
+ if (!ret)
+   return ret;
+
+ page = virt_to_head_page(ret);
+
+ if (!mem_cgroup_new_kmem_page(page, flags)) {
+   put_page(page);
+   return NULL;
+ }
}

```

```
+
+ return ret;
+}
+
+/**
+ * Calling this on allocated memory will check that the memory
+ * is expected to be in use, and print warnings if not.
@@ -293,7 +322,7 @@ static __always_inline void *kmalloc(size_t size, gfp_t flags)
return kmalloc_large(size, flags);

if (!(flags & SLUB_DMA)) {
- struct kmem_cache *s = kmalloc_slab(size);
+ struct kmem_cache *s = kmalloc_slab(flags, size);

if (!s)
return ZERO_SIZE_PTR;
@@ -326,7 +355,7 @@ static __always_inline void *kmalloc_node(size_t size, gfp_t flags, int
node)
{
if (__builtin_constant_p(size) &&
size <= SLUB_MAX_SIZE && !(flags & SLUB_DMA)) {
- struct kmem_cache *s = kmalloc_slab(size);
+ struct kmem_cache *s = kmalloc_slab(flags, size);

if (!s)
return ZERO_SIZE_PTR;
diff --git a/mm/slub.c b/mm/slub.c
index 640872f..730e69f 100644
--- a/mm/slub.c
+++ b/mm/slub.c
@@ -1283,11 +1283,39 @@ static inline struct page *alloc_slab_page(gfp_t flags, int node,
return alloc_pages_exact_node(node, flags, order);
}

+static inline unsigned long size_in_bytes(unsigned int order)
+{
+ return (1 << order) << PAGE_SHIFT;
+}
+
+
+
+#ifdef CONFIG_CGROUP_MEM_RES_CTLR_KMEM
+static void kmem_cache_inc_ref(struct kmem_cache *s)
+{
+ if (s->memcg_params.memcg)
+ atomic_inc(&s->memcg_params.refcnt);
+}
+
+static void kmem_cache_drop_ref(struct kmem_cache *s)
+{
+ if (s->memcg_params.memcg)
```

```
+ atomic_dec(&s->memcg_params.refcnt);
+}
+#else
+static inline void kmem_cache_inc_ref(struct kmem_cache *s)
+{
+}
+static inline void kmem_cache_drop_ref(struct kmem_cache *s)
+{
+}
+#endif
+
+
+
+static struct page *allocate_slab(struct kmem_cache *s, gfp_t flags, int node)
+{
+- struct page *page;
+ struct page *page = NULL;
+ struct kmem_cache_order_objects oo = s->oo;
+ gfp_t alloc_gfp;
+ unsigned int memcg_allowed = oo_order(oo);
+
+ flags &= gfp_allowed_mask;
@@ -1296,13 +1324,29 @@ static struct page *allocate_slab(struct kmem_cache *s, gfp_t flags,
int node)
+
+ flags |= s->allocflags;
+
+- /*
+- * Let the initial higher-order allocation fail under memory pressure
+- * so we fall-back to the minimum order allocation.
+- */
+ alloc_gfp = (flags | __GFP_NOWARN | __GFP_NORETRY) & ~__GFP_NOFAIL;
+ memcg_allowed = oo_order(oo);
+ if (!mem_cgroup_charge_slab(s, flags, size_in_bytes(memcg_allowed))) {
+
+ memcg_allowed = oo_order(s->min);
+ if (!mem_cgroup_charge_slab(s, flags,
+ size_in_bytes(memcg_allowed))) {
+ if (flags & __GFP_WAIT)
+ local_irq_disable();
+ return NULL;
+ }
+ }
+
+ if (memcg_allowed == oo_order(oo)) {
+ /*
+ * Let the initial higher-order allocation fail under memory
```

```

+ * pressure so we fall-back to the minimum order allocation.
+ */
+ alloc_gfp = (flags | __GFP_NOWARN | __GFP_NORETRY) &
+   ~__GFP_NOFAIL;
+
+ page = alloc_slab_page(alloc_gfp, node, oo);
+ }

- page = alloc_slab_page(alloc_gfp, node, oo);
  if (unlikely(!page)) {
    oo = s->min;
    /*
@@ -1313,13 +1357,25 @@ static struct page *allocate_slab(struct kmem_cache *s, gfp_t flags,
    int node)

    if (page)
      stat(s, ORDER_FALLBACK);
+   /*
+   * We reserved more than we used, time to give it back
+   */
+   if (page && memcg_allowed != oo_order(oo)) {
+     unsigned long delta;
+     delta = memcg_allowed - oo_order(oo);
+     mem_cgroup_uncharge_slab(s, size_in_bytes(delta));
+   }
+ }

  if (flags & __GFP_WAIT)
    local_irq_disable();

- if (!page)
+ if (!page) {
+   mem_cgroup_uncharge_slab(s, size_in_bytes(memcg_allowed));
+   return NULL;
+ }
+
+ kmem_cache_inc_ref(s);

  if (kmemcheck_enabled
      && !(s->flags & (SLAB_NOTRACK | DEBUG_DEFAULT_FLAGS))) {
@@ -1419,6 +1475,9 @@ static void __free_slab(struct kmem_cache *s, struct page *page)
    if (current->reclaim_state)
      current->reclaim_state->reclaimed_slab += pages;
    __free_pages(page, order);
+
+   mem_cgroup_uncharge_slab(s, (1 << order) << PAGE_SHIFT);
+   kmem_cache_drop_ref(s);
+ }

```

```

#define need_reserve_slab_rcu    \
@@ -2310,6 +2369,9 @@ static __always_inline void *slab_alloc(struct kmem_cache *s,
    if (slab_pre_alloc_hook(s, gfpflags))
        return NULL;

+ rcu_read_lock();
+ s = mem_cgroup_get_kmem_cache(s, gfpflags);
+ rcu_read_unlock();
redo:

/*
@@ -3372,9 +3434,15 @@ static void *kmalloc_large_node(size_t size, gfp_t flags, int node)

    flags |= __GFP_COMP | __GFP_NOTRACK;
    page = alloc_pages_node(node, flags, get_order(size));
- if (page)
+ if (!page)
+ goto out;
+
+ if (!mem_cgroup_new_kmem_page(page, flags))
+ put_page(page);
+ else
    ptr = page_address(page);

+out:
    kmemleak_alloc(ptr, size, 1, flags);
    return ptr;
}
@@ -3476,6 +3544,7 @@ void kfree(const void *x)
    if (unlikely(!PageSlab(page))) {
        BUG_ON(!PageCompound(page));
        kmemleak_free(x);
+ mem_cgroup_free_kmem_page(page);
        put_page(page);
        return;
    }
}

```

1.7.7.6
