Posted by Christian Blaich on Mon, 18 Jun 2012 16:18:02 GMT
View Forum Message <> Reply to Message

-----BEGIN PGP SIGNED MESSAGE-----
Hash: SHA1

Hi guys,

i'm working on a monitoring solution for my hardwarenodes.
Hosts A with Debian Squeeze and linux-image-2.6.32-5-openvz-amd64 from
the Debian Repository and Hosts B Debian Squeeze with Proxmox
2.6.32-12-pve from the Proxmoxrepo.
Both working with ovz Containers. When i'm trying to check netstat on
Hosts A i see the Connections from the Hardwarenode, such as ntp. Hosts
B (Proxmox) tells me the whole Connectiontree including every VM connection.
That result is bad for my checks and i don't wanna write seperate checks
for A & B.
Any ideas ?

-----BEGIN PGP SIGNATURE-----
Version: GnuPG/MacGPG2 v2.0.17 (Darwin)
Comment: GPGTools - http://gpgtools.org
Comment: Using GnuPG with Mozilla - http://enigmail.mozdev.org/

iQEcBAEBAgAGBQJP31S5AAoJENzPm0AOTN5bJzgIAJPEnA0oUaBIDWwlpkT1 OrCv
HKlAKDFiqgkKZ7rVvDyxm7hgqRJNvgnq76c/RbF9dOXt71XiP10EtHGamJWs j1XN
72Sqru6AhLCUakk1hqaNXITTs963VGXx9ZqwtghXct5yEFte1nYEgzCvUbMb q8r3
vpkCb1rViomKtykCZGPMDiHd08K91dcWEEtqGDr1is3WDw2rLX7VxThpM0DD Un6M
o2UZCcDQxW2EI3FbhRwEAFywjgWaMeh+u4tWIcP3mOhvtt2ANcKjlso2c7Kb Vhxv
us2Y5YXuawj1BGJ0qfW1s8KdqxfopSYJ4yVyKIFyTB+KADibsEo6NT7BBs4l nOA=
=g/TT
-----END PGP SIGNATURE-----