
Subject: [PATCH 11/11] protect architectures where THREAD_SIZE >= PAGE_SIZE against fork bombs

Posted by [Glauber Costa](#) on Mon, 25 Jun 2012 14:15:28 GMT

[View Forum Message](#) <> [Reply to Message](#)

Because those architectures will draw their stacks directly from the page allocator, rather than the slab cache, we can directly pass `__GFP_KMEMCG` flag, and issue the corresponding `free_pages`.

This code path is taken when the architecture doesn't define `CONFIG_ARCH_THREAD_INFO_ALLOCATOR` (only ia64 seems to), and has `THREAD_SIZE >= PAGE_SIZE`. Luckily, most - if not all - of the remaining architectures fall in this category.

This will guarantee that every stack page is accounted to the memcg the process currently lives on, and will have the allocations to fail if they go over limit.

For the time being, I am defining a new variant of `THREADINFO_GFP`, not to mess with the other path. Once the slab is also tracked by memcg, we can get rid of that flag.

Tested to successfully protect against `:(){ :|& };:`

Signed-off-by: Glauber Costa <glommer@parallels.com>

CC: Christoph Lameter <cl@linux.com>

CC: Pekka Enberg <penberg@cs.helsinki.fi>

CC: Michal Hocko <mhocko@suse.cz>

CC: Kamezawa Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

CC: Johannes Weiner <hannes@cmpxchg.org>

CC: Suleiman Souhlal <suleiman@google.com>

CC: Frederic Weisbecker <fweisbec@redhat.com>

include/linux/thread_info.h | 6 ++++++

kernel/fork.c | 4 ++--

2 files changed, 8 insertions(+), 2 deletions(-)

diff --git a/include/linux/thread_info.h b/include/linux/thread_info.h

index ccc1899..914ec07 100644

--- a/include/linux/thread_info.h

+++ b/include/linux/thread_info.h

@@ -61,6 +61,12 @@ extern long do_no_restart_syscall(struct restart_block *parm);

define THREADINFO_GFP (GFP_KERNEL | __GFP_NOTRACK)

#endif

+#ifdef CONFIG_CGROUP_MEM_RES_CTLR_KMEM

+# define THREADINFO_GFP_ACCOUNTED (THREADINFO_GFP | __GFP_KMEMCG)

+#else

```

+# define THREADINFO_GFP_ACCOUNTED (THREADINFO_GFP)
+#endif
+
+/*
+ * flag set/clear/test wrappers
+ * - pass TIF_xxxx constants to these functions
diff --git a/kernel/fork.c b/kernel/fork.c
index ab5211b..06b414f 100644
--- a/kernel/fork.c
+++ b/kernel/fork.c
@@ -142,7 +142,7 @@ void __weak arch_release_thread_info(struct thread_info *ti) { }
static struct thread_info *alloc_thread_info_node(struct task_struct *tsk,
int node)
{
- struct page *page = alloc_pages_node(node, THREADINFO_GFP,
+ struct page *page = alloc_pages_node(node, THREADINFO_GFP_ACCOUNTED,
THREAD_SIZE_ORDER);

return page ? page_address(page) : NULL;
@@ -151,7 +151,7 @@ static struct thread_info *alloc_thread_info_node(struct task_struct *tsk,
static inline void free_thread_info(struct thread_info *ti)
{
arch_release_thread_info(ti);
- free_pages((unsigned long)ti, THREAD_SIZE_ORDER);
+ free_accounted_pages((unsigned long)ti, THREAD_SIZE_ORDER);
}
# else
static struct kmem_cache *thread_info_cache;
--
1.7.10.2

```
