
Subject: [PATCH v3 11/11] NFS: get net after idr allocation
Posted by [Stanislav Kinsbursky](#) on Tue, 03 Jul 2012 16:20:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

Allocation can fail. So instead of put net in case of failure, get net after allocation.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfs/client.c | 3 ++-

1 files changed, 2 insertions(+), 1 deletions(-)

diff --git a/fs/nfs/client.c b/fs/nfs/client.c

index d8c918b..d17aa10 100644

--- a/fs/nfs/client.c

+++ b/fs/nfs/client.c

@@ -175,7 +175,7 @@ static struct nfs_client *nfs_alloc_client(const struct nfs_client_initdata *cl_
clp->cl_rpcclient = ERR_PTR(-EINVAL);

clp->cl_proto = cl_init->proto;
- clp->cl_net = get_net(cl_init->net);
+ clp->cl_net = cl_init->net;

#ifdef CONFIG_NFS_V4

err = nfs_get_cb_ident_idr(clp, cl_init->minorversion);
@@ -189,6 +189,7 @@ static struct nfs_client *nfs_alloc_client(const struct nfs_client_initdata *cl_
clp->cl_minorversion = cl_init->minorversion;
clp->cl_mvops = nfs_v4_minor_ops[cl_init->minorversion];
#endif
+ get_net(clp->cl_net);
cred = rpc_lookup_machine_cred("");
if (!IS_ERR(cred))
clp->cl_machine_cred = cred;
