
Subject: Re: [PATCH] NFS: put net in case of idr allocation failure
Posted by [Stanislav Kinsbursky](#) on Mon, 20 Aug 2012 16:14:54 GMT
[View Forum Message](#) <> [Reply to Message](#)

> On Mon, 2012-08-20 at 17:43 +0400, Stanislav Kinsbursky wrote:
>> Put net reference we got in nfs_alloc_client() on error path.
>>
>> Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>
>> ---
>> fs/nfs/nfs4client.c | 1 +
>> 1 files changed, 1 insertions(+), 0 deletions(-)
>>
>> diff --git a/fs/nfs/nfs4client.c b/fs/nfs/nfs4client.c
>> index cbcdfaf..b895629 100644
>> --- a/fs/nfs/nfs4client.c
>> +++ b/fs/nfs/nfs4client.c
>> @@ -74,6 +74,7 @@ struct nfs_client *nfs4_alloc_client(const struct nfs_client_initdata
>> *cl_init)
>> return clp;
>>
>> error:
>> + put_net(clp->cl_net);
>> kfree(clp);
>> return ERR_PTR(err);
>> }
>
>
> No, that isn't anywhere near sufficient.
>
> The correct thing to do here is to replace the kfree with a call to
> nfs_free_client(), which will also clean up the allocation of
> cl_hostname, put the module, etc.
>

Sure, you are right.

--

Best regards,
Stanislav Kinsbursky
