

---

Subject: Re: ploop and mount options  
Posted by [kir](#) on Sat, 08 Sep 2012 09:19:15 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

On 09/06/2012 03:53 PM, Corin Langosch wrote:

> Hi again,  
>  
> just a small follow up on this:  
>  
> Inside the the container I'm able to change the barrier mount option  
> with:  
>  
> "mount -o remount,barrier=0 /" or "mount -o remount,barrier=1 /"  
>  
> But changing other options like "noatime" (mount -o remount,noatime /)  
> fails with "mount: permission denied".  
>  
> Now I wonder if this is intended or a bug? Why allow changing barrier  
> and deny noatime option?

Well, I can't tell why it lets you remount with barrier but does not let you remount with noatime.

But I can tell noatime is not needed nowadays, since relatime is used by default and makes much more sense.

You can file a bug to [bugzilla.openvz.org](http://bugzilla.openvz.org), component ploop

>  
> BTW: I still haven't found a way to specify mount options in the  
> container's config :(

Again, file a bug (enhancement) to [bugzilla.openvz.org](http://bugzilla.openvz.org), component vzctl.

>  
> Corin  
>  
> On 03.07.2012 at 09:52 +0200, Corin Langosch <[info@corinlangosch.com](mailto:info@corinlangosch.com)>  
> wrote:  
>> Hi there,  
>>  
>> Is there any way to specify mount options for the container's root  
>> filesystem in the container's config when using ploop?  
>>  
>> So a normal options string like  
>> " noatime,data=writeback,journal\_async\_commit,barrier=0,errors=remount-ro "  
>>  
>>

>> Thanks for any hints :)

>>

>> Corin

---