
Subject: [PATCH v3 08/13] res_counter: return amount of charges after
res_counter_uncharge

Posted by [Glauber Costa](#) on Tue, 18 Sep 2012 14:04:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

It is useful to know how many charges are still left after a call to
res_counter_uncharge. While it is possible to issue a res_counter_read
after uncharge, this is racy. It would be better if uncharge itself
would tell us what the current status is.

Since the current return value is void, we don't need to worry about
anything breaking due to this change: nobody relied on that, and only
users appearing from now on will be checking this value.

Signed-off-by: Glauber Costa <glommer@parallels.com>

CC: Michal Hocko <mhocko@suse.cz>

CC: Johannes Weiner <hannes@cmpxchg.org>

CC: Suleiman Souhlal <suleiman@google.com>

CC: Kamezawa Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

```
Documentation/cgroups/resource_counter.txt | 7 ++++---
include/linux/res_counter.h                | 12 ++++++-----
kernel/res_counter.c                       | 20 ++++++-----
3 files changed, 24 insertions(+), 15 deletions(-)
```

```
diff --git a/Documentation/cgroups/resource_counter.txt
```

```
b/Documentation/cgroups/resource_counter.txt
```

```
index 0c4a344..c4d99ed 100644
```

```
--- a/Documentation/cgroups/resource_counter.txt
```

```
+++ b/Documentation/cgroups/resource_counter.txt
```

```
@@ -83,16 +83,17 @@ to work with it.
```

```
res_counter->lock internally (it must be called with res_counter->lock
held). The force parameter indicates whether we can bypass the limit.
```

```
- e. void res_counter_uncharge[_locked]
```

```
+ e. u64 res_counter_uncharge[_locked]
```

```
(struct res_counter *rc, unsigned long val)
```

When a resource is released (freed) it should be de-accounted
from the resource counter it was accounted to. This is called

- "uncharging".

+ "uncharging". The return value of this function indicate the amount

+ of charges still present in the counter.

The _locked routines imply that the res_counter->lock is taken.

```
- f. void res_counter_uncharge_until
```

```
+ f. u64 res_counter_uncharge_until
```

```
(struct res_counter *rc, struct res_counter *top,  
unsigned long val)
```

```
diff --git a/include/linux/res_counter.h b/include/linux/res_counter.h
```

```
index 7d7fbe2..4b173b6 100644
```

```
--- a/include/linux/res_counter.h
```

```
+++ b/include/linux/res_counter.h
```

```
@ @ -130,14 +130,16 @ @ int res_counter_charge_nofail(struct res_counter *counter,  
*
```

```
* these calls check for usage underflow and show a warning on the console
```

```
* _locked call expects the counter->lock to be taken
```

```
+ *
```

```
+ * returns the total charges still present in @counter.
```

```
*/
```

```
-void res_counter_uncharge_locked(struct res_counter *counter, unsigned long val);
```

```
-void res_counter_uncharge(struct res_counter *counter, unsigned long val);
```

```
+u64 res_counter_uncharge_locked(struct res_counter *counter, unsigned long val);
```

```
+u64 res_counter_uncharge(struct res_counter *counter, unsigned long val);
```

```
-void res_counter_uncharge_until(struct res_counter *counter,
```

```
- struct res_counter *top,
```

```
- unsigned long val);
```

```
+u64 res_counter_uncharge_until(struct res_counter *counter,
```

```
+ struct res_counter *top,
```

```
+ unsigned long val);
```

```
/**
```

```
* res_counter_margin - calculate chargeable space of a counter
```

```
* @cnt: the counter
```

```
diff --git a/kernel/res_counter.c b/kernel/res_counter.c
```

```
index ad581aa..7b3d6dc 100644
```

```
--- a/kernel/res_counter.c
```

```
+++ b/kernel/res_counter.c
```

```
@ @ -86,33 +86,39 @ @ int res_counter_charge_nofail(struct res_counter *counter, unsigned long  
val,
```

```
return __res_counter_charge(counter, val, limit_fail_at, true);
```

```
}
```

```
-void res_counter_uncharge_locked(struct res_counter *counter, unsigned long val)
```

```
+u64 res_counter_uncharge_locked(struct res_counter *counter, unsigned long val)
```

```
{
```

```
if (WARN_ON(counter->usage < val))
```

```
val = counter->usage;
```

```
counter->usage -= val;
```

```
+ return counter->usage;
```

```
}
```

```

-void res_counter_uncharge_until(struct res_counter *counter,
-    struct res_counter *top,
-    unsigned long val)
+u64 res_counter_uncharge_until(struct res_counter *counter,
+    struct res_counter *top,
+    unsigned long val)
{
    unsigned long flags;
    struct res_counter *c;
+ u64 ret = 0;

    local_irq_save(flags);
    for (c = counter; c != top; c = c->parent) {
+ u64 r;
        spin_lock(&c->lock);
- res_counter_uncharge_locked(c, val);
+ r = res_counter_uncharge_locked(c, val);
+ if (c == counter)
+     ret = r;
        spin_unlock(&c->lock);
    }
    local_irq_restore(flags);
+ return ret;
}

-void res_counter_uncharge(struct res_counter *counter, unsigned long val)
+u64 res_counter_uncharge(struct res_counter *counter, unsigned long val)
{
- res_counter_uncharge_until(counter, NULL, val);
+ return res_counter_uncharge_until(counter, NULL, val);
}

static inline unsigned long long *
--

```

1.7.11.4
