Subject: [PATCH v4 19/19] Add slab-specific documentation about the kmem controller

Posted by Glauber Costa on Fri, 12 Oct 2012 13:41:13 GMT

View Forum Message <> Reply to Message

Signed-off-by: Glauber Costa <glommer@parallels.com>

CC: Christoph Lameter <cl@linux.com>

CC: Pekka Enberg <penberg@cs.helsinki.fi>

CC: Michal Hocko <mhocko@suse.cz>

CC: Kamezawa Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

CC: Johannes Weiner <hannes@cmpxchg.org>

CC: Suleiman Souhlal <suleiman@google.com>

CC: Tejun Heo <tj@kernel.org>

Documentation/cgroups/memory.txt | 7 ++++++

1 file changed, 7 insertions(+)

diff --git a/Documentation/cgroups/memory.txt b/Documentation/cgroups/memory.txt index dd15be8..95e4809 100644

- --- a/Documentation/cgroups/memory.txt
- +++ b/Documentation/cgroups/memory.txt
- @ @ -300,6 +300,13 @ @ to trigger slab reclaim when those limits are reached. kernel memory, we prevent new processes from being created when the kernel memory usage is too high.
- +* slab pages: pages allocated by the SLAB or SLUB allocator are tracked. A copy +of each kmem_cache is created everytime the cache is touched by the first time +from inside the memcg. The creation is done lazily, so some objects can still be +skipped while the cache is being created. All objects in a slab page should +belong to the same memcg. This only fails to hold when a task is migrated to a +different memcg during the page allocation by the cache.

+ *.

--

1.7.11.4

^{*} sockets memory pressure: some sockets protocols have memory pressure thresholds. The Memory Controller allows them to be controlled individually per cgroup, instead of globally.