

---

Subject: [PATCH v4 05/19] slab: don't preemptively remove element from list in cache destroy

Posted by [Glauber Costa](#) on Fri, 12 Oct 2012 13:40:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

After the slab/slub/slob merge, we are deleting the element from the slab\_cache lists, and then if the destruction fail, we add it back again. This behavior was present in some caches, but not in others, if my memory doesn't fail me.

I, however, see no reason why we need to do so, since we are now locked during the whole deletion (which wasn't necessarily true before). I propose a simplification in which we delete it only when there is no more going back, so we don't need to add it again.

Signed-off-by: Glauber Costa <glommer@parallels.com>

CC: Christoph Lameter <cl@linux.com>

CC: Pekka Enberg <penberg@cs.helsinki.fi>

CC: Michal Hocko <mhocko@suse.cz>

CC: Kamezawa Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

CC: Johannes Weiner <hannes@cmpxchg.org>

CC: Suleiman Souhlal <suleiman@google.com>

CC: Tejun Heo <tj@kernel.org>

---

mm/slab\_common.c | 5 ++---

1 file changed, 2 insertions(+), 3 deletions(-)

diff --git a/mm/slab\_common.c b/mm/slab\_common.c

index 1ee1d6f..bf4b4f1 100644

--- a/mm/slab\_common.c

+++ b/mm/slab\_common.c

@@ -174,16 +174,15 @@ void kmem\_cache\_destroy(struct kmem\_cache \*s)

mutex\_lock(&slab\_mutex);

s->refcount--;

if (!s->refcount) {

- list\_del(&s->list);

-

if (!\_\_kmem\_cache\_shutdown(s)) {

if (s->flags & SLAB\_DESTROY\_BY\_RCU)

rcu\_barrier();

+ list\_del(&s->list);

+

kfree(s->name);

kmem\_cache\_free(kmem\_cache, s);

} else {

- list\_add(&s->list, &slab\_caches);

printk(KERN\_ERR "kmem\_cache\_destroy %s: Slab cache still has objects\n",

```
s->name);  
dump_stack();  
--  
1.7.11.4
```

---