
Subject: [PATCH v5 00/14] kmem controller for memcg.
Posted by [Glauber Costa](#) on Tue, 16 Oct 2012 10:16:37 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

This is the first part of the kernel memory controller for memcg. It has been discussed many times, and I consider this stable enough to be on tree. A follow up to this series are the patches to also track slab memory. They are not included here because I believe we could benefit from merging them separately for better testing coverage. If there are any issues preventing this to be merged, let me know. I'll be happy to address them.

*v5: - changed charged order, kmem charged first.
- minor nits and comments merged.

*v4: - kmem_accounted can no longer become unlimited
- kmem_accounted can no longer become limited, if group has children.
- documentation moved to this patchset
- more style changes
- css_get in charge path to ensure task won't move during charge

*v3:
- Changed function names to match memcg's
- avoid doing get/put in charge/uncharge path
- revert back to keeping the account enabled after it is first activated

Numbers can be found at <https://lkml.org/lkml/2012/9/13/239>

A (throwaway) git tree with them is placed at:

`git://git.kernel.org/pub/scm/linux/kernel/git/glommer/memcg.git` kmemcg-stack

A general explanation of what this is all about follows:

The kernel memory limitation mechanism for memcg concerns itself with disallowing potentially non-reclaimable allocations to happen in exaggerate quantities by a particular set of processes (cgroup). Those allocations could create pressure that affects the behavior of a different and unrelated set of processes.

Its basic working mechanism is to annotate some allocations with the `_GFP_KMEMCG` flag. When this flag is set, the current process allocating will have its memcg identified and charged against. When reaching a specific limit, further allocations will be denied.

One example of such problematic pressure that can be prevented by this work is a fork bomb conducted in a shell. We prevent it by noting that processes use a limited amount of stack pages. Seen this way, a fork bomb is just a special

case of resource abuse. If the offender is unable to grab more pages for the stack, no new processes can be created.

There are also other things the general mechanism protects against. For example, using too much of pinned dentry and inode cache, by touching files and leaving them in memory forever.

In fact, a simple:

```
while true; do mkdir x; cd x; done
```

can halt your system easily because the file system limits are hard to reach (big disks), but the kernel memory is not. Those are examples, but the list certainly don't stop here.

An important use case for all that, is concerned with people offering hosting services through containers. In a physical box we can put a limit to some resources, like total number of processes or threads. But in an environment where each independent user gets its own piece of the machine, we don't want a potentially malicious user to destroy good users' services.

This might be true for systemd as well, that now groups services inside cgroups. They generally want to put forward a set of guarantees that limits the running service in a variety of ways, so that if they become badly behaved, they won't interfere with the rest of the system.

There is, of course, a cost for that. To attempt to mitigate that, static branches are used to make sure that even if the feature is compiled in with potentially a lot of memory cgroups deployed this code will only be enabled after the first user of this service configures any limit. Limits lower than the user limit effectively means there is a separate kernel memory limit that may be reached independently than the user limit. Values equal or greater than the user limit implies only that kernel memory is tracked. This provides a unified vision of "maximum memory", be it kernel or user memory. Because this is all default-off, existing deployments will see no change in behavior.

Glauber Costa (12):

- memcg: change defines to an enum
- kmem accounting basic infrastructure
- Add a __GFP_KMEMCG flag
- memcg: kmem controller infrastructure
- mm: Allocate kernel pages to the right memcg
- res_counter: return amount of charges after res_counter_uncharge
- memcg: kmem accounting lifecycle management
- memcg: use static branches when code not in use
- memcg: allow a memcg with kmem charges to be destructed.
- execute the whole memcg freeing in free_worker
- protect architectures where THREAD_SIZE >= PAGE_SIZE against fork

bombs

Add documentation about the kmem controller

Suleiman Souhlal (2):

memcg: Make it possible to use the stock for more than one page.

memcg: Reclaim when more than one page needed.

```
Documentation/cgroups/memory.txt      | 58 +-  
Documentation/cgroups/resource_counter.txt | 7 +-  
include/linux/gfp.h                   | 6 +-  
include/linux/memcontrol.h            | 100 ++++++  
include/linux/res_counter.h           | 12 +-  
include/linux/thread_info.h          | 2 +  
include/trace/events/gfpflags.h      | 1 +  
kernel/fork.c                          | 4 +-  
kernel/res_counter.c                  | 20 +-  
mm/memcontrol.c                       | 553 ++++++-----  
mm/page_alloc.c                       | 35 ++  
11 files changed, 717 insertions(+), 81 deletions(-)
```

--

1.7.11.7
