
Subject: [PATCH v7 04/10] ipc: add new SHM_SET command for sys_shmctl() call

Posted by Stanislav Kinsbursky on Thu, 18 Oct 2012 10:22:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

New SHM_SET command will be interpreted exactly as IPC_SET, but also will update key, cuid and cgid values. IOW, it allows to change existent key value. The fact, that key is not used is checked before update. Otherwise -EEXIST is returned.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

```
include/uapi/linux/shm.h |  1 +
ipc/compat.c           |  1 +
ipc/shm.c              | 14 ++++++++-----
security/selinux/hooks.c|  1 +
security/smack/smack_lsm.c|  1 +
5 files changed, 16 insertions(+), 2 deletions(-)
```

```
diff --git a/include/uapi/linux/shm.h b/include/uapi/linux/shm.h
```

```
index ec36fa1..d7413fd 100644
```

```
--- a/include/uapi/linux/shm.h
```

```
+++ b/include/uapi/linux/shm.h
```

```
@@ -56,6 +56,7 @@ struct shmid_ds {  
 /* ipcs ctl commands */  
 #define SHM_STAT 13  
 #define SHM_INFO 14  
+#define SHM_SET 15
```

```
/* Obsolete, used only for backwards compatibility */
```

```
struct shminfo {
```

```
diff --git a/ipc/compat.c b/ipc/compat.c
```

```
index af30d13..35c750d 100644
```

```
--- a/ipc/compat.c
```

```
+++ b/ipc/compat.c
```

```
@@ -692,6 +692,7 @@ long compat_sys_shmctl(int first, int second, void __user *uptr)
```

```
    case IPC_SET:
```

```
+   case SHM_SET:
```

```
     if (version == IPC_64) {  
       err = get_compat_shmid64_ds(&s64, uptr);  
     } else {
```

```
diff --git a/ipc/shm.c b/ipc/shm.c
```

```
index 80b0046..650911e 100644
```

```
--- a/ipc/shm.c
```

```
+++ b/ipc/shm.c
```

```
@@ -636,6 +636,9 @@ copy_shmid_from_user(struct shmid64_ds *out, void __user *buf, int  
version)
```

```

out->shm_perm.uid = tbuf_old.shm_perm.uid;
out->shm_perm.gid = tbuf_old.shm_perm.gid;
out->shm_perm.mode = tbuf_old.shm_perm.mode;
+ out->shm_perm.cuid = tbuf_old.shm_perm.cuid;
+ out->shm_perm.cgid = tbuf_old.shm_perm.cgid;
+ out->shm_perm.key = tbuf_old.shm_perm.key;

return 0;
}

@@ -740,12 +743,13 @@ static int shmctl_down(struct ipc_namespace *ns, int shmid, int cmd,
struct shmid_kernel *shp;
int err;

- if (cmd == IPC_SET) {
+ if (cmd == IPC_SET || cmd == SHM_SET) {
if (copy_shmid_from_user(&shmid64, buf, version))
    return -EFAULT;
}

- ipcp = ipcctl_pre_down(ns, &shm_ids(ns), shmid, cmd,
+ ipcp = ipcctl_pre_down(ns, &shm_ids(ns), shmid,
+     (cmd != SHM_SET) ? cmd : IPC_SET,
&shmid64.shm_perm, 0);
if (IS_ERR(ipcp))
    return PTR_ERR(ipcp);
@@ -759,6 +763,11 @@ static int shmctl_down(struct ipc_namespace *ns, int shmid, int cmd,
case IPC_RMID:
    do_shm_rmid(ns, ipcp);
    goto out_up;
+ case SHM_SET:
+     err = ipc_update_key(&shm_ids(ns), &shmid64.shm_perm, ipcp);
+     if (err)
+         break;
+     /* fall through */
case IPC_SET:
    err = ipc_update_perm(&shmid64.shm_perm, ipcp);
    if (err)
@@ -938,6 +947,7 @@ SYSCALL_DEFINE3(shmctl, int, shmid, int, cmd, struct shmid_ds __user
*, buf)
}
case IPC_RMID:
case IPC_SET:
+ case SHM_SET:
    err = shmctl_down(ns, shmid, cmd, buf, version);
    return err;
default:
diff --git a/security/selinux/hooks.c b/security/selinux/hooks.c
index 24ab414..62b2447 100644

```

```
--- a/security/selinux/hooks.c
+++ b/security/selinux/hooks.c
@@ -5027,6 +5027,7 @@ static int selinux_shm_shmctl(struct shmid_kernel *shp, int cmd)
 perms = SHM__GETATTR | SHM__ASSOCIATE;
 break;
 case IPC_SET:
+ case SHM_SET:
 perms = SHM__SETATTR;
 break;
 case SHM_LOCK:
diff --git a/security/smack/smack_lsm.c b/security/smack/smack_lsm.c
index 38be92c..c7eabc9 100644
--- a/security/smack/smack_lsm.c
+++ b/security/smack/smack_lsm.c
@@ -2121,6 +2121,7 @@ static int smack_shm_shmctl(struct shmid_kernel *shp, int cmd)
 may = MAY_READ;
 break;
 case IPC_SET:
+ case SHM_SET:
 case SHM_LOCK:
 case SHM_UNLOCK:
 case IPC_RMID:
```
