Subject: Re: [PATCH v7 09/10] IPC: message queue copy feature introduced Posted by Stanislav Kinsbursky on Thu, 18 Oct 2012 12:05:52 GMT

View Forum Message <> Reply to Message

```
>>>> A naive question, because I have not followed C/R closely. How do you
>>>> deal with the case that other processes may be reading from the queue?
>>>> (Or is that disabled during checkpointing?)
>>>>
>>>>
>>>> To be honest, in this case behaviour in user-space is unpredictable.
>>>> I.e. if you have, for example, 5 messages in gueue and going to peek them
>>>> all, and another process is reading the queue in the same time, then,
>>> most
>>>> probably, you won't peek all the 5 and receive ENOMSG.
>>>> But this case can be easily handled by user-space application (number of
>>>> messages in queue can be discovered before peeking).
>>> Note, that in CRIU IPC resources will be collected when all processes to
>>>> migrate are frozen.
>>>
>>>
>>> Perhaps I am missing something fundamental, but how can C/R sanely do
>>> anything at all here?
>>>
>>> For example, suppose a process reads and processes a message after you
>>> read it with MSG_COPY. Then the remaining messages are all shifted by
>>> one position, and you are going to miss reading one of them. IIUC the
>>> idea of MSG COPY is to allow you to retrieve a copy of all messages in
>>> the list. It sounds like there's no way this can be done reliably. So,
>>> what possible use does the operation have?
>>>
>>
>> First of all, this problem exist as is regardless to C/R feature or this
>> patch set. If you share some resource (like message queue in this particular
>> case) system-wide, then any process A can read out a message, which was send
>> by process B to process C. So, when processes uses IPC message queues, they
>> should be designed to handle such failures.
>> Second, it's up to user-space how to handle such things. It's implied, that
>> user, trying to migrate some process, holding one end of gueue, will also
>> migrate another process, holding second end.
>> Third, there is IPC namespace, which isolates IPC objects. It can be used
>> for safe migration of process tree.
> Is there somewhere a *detailed* description of how this feature would
> be used? Lacking that, it's really hard to see how anything sane and
```

> reliable can be done with MSG_COPY.

These patches are used by CRIU already. So, you can have a look at the CRIU source code:

 $\label{lem:http://git.criu.org/?p=crtools.git} $$ $a=blob; f=ipc_ns.c; h=9e259 fefcfc04ec0556bb722921545552e1c69f 3; hb=HEAD $$$

Sanity and reliability on the level you are talking about can be achieved, only if you'll freeze all message users before peeking.

--

Best regards, Stanislav Kinsbursky