

---

Subject: Re: [PATCH v6 03/10] ipc: segment key change helper introduced  
Posted by [Serge E. Hallyn](#) on Tue, 23 Oct 2012 16:19:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Quoting Stanislav Kinsbursky ([skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)):

> This patch introduces existent segment key changing infrastructure.  
> New function ipc\_update\_key() can be used change segment key, cuid, cgid  
> values. It checks for that new key is not used (except IPC\_PRIVATE) prior to  
> set it on existent.  
> To make this possible, added copying of this fields from user-space in  
> \_\_get\_compat\_ipc\_perm() and \_\_get\_compat\_ipc64\_perm() functions. Also segment  
> search by key and lock were splitted into different functions, because  
> ipc\_update\_key() doesn't need to lock the segment during check that new key is  
> not used.  
>  
> Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

Acked-by: Serge E. Hallyn <[serge.hallyn@ubuntu.com](mailto:serge.hallyn@ubuntu.com)>

```
> ---  
> ipc/compat.c |  6 ++++++  
> ipc/util.c   | 51 ++++++-----  
> ipc/util.h   |  2 ++  
> 3 files changed, 56 insertions(+), 3 deletions(-)  
>  
> diff --git a/ipc/compat.c b/ipc/compat.c  
> index ad9518e..af30d13 100644  
> --- a/ipc/compat.c  
> +++ b/ipc/compat.c  
> @@ -144,6 +144,9 @@ static inline int __get_compat_ipc64_perm(struct ipc64_perm *p64,  
> err = __get_user(p64->uid, &up64->uid);  
> err |= __get_user(p64->gid, &up64->gid);  
> err |= __get_user(p64->mode, &up64->mode);  
> + err |= __get_user(p64->cuid, &up64->cuid);  
> + err |= __get_user(p64->cgid, &up64->cgid);  
> + err |= __get_user(p64->key, &up64->key);  
> return err;  
> }  
>  
> @@ -155,6 +158,9 @@ static inline int __get_compat_ipc_perm(struct ipc64_perm *p,  
> err = __get_user(p->uid, &up->uid);  
> err |= __get_user(p->gid, &up->gid);  
> err |= __get_user(p->mode, &up->mode);  
> + err |= __get_user(p->cuid, &up->cuid);  
> + err |= __get_user(p->cgid, &up->cgid);  
> + err |= __get_user(p->key, &up->key);  
> return err;  
> }
```

```

>
> diff --git a/ipc/util.c b/ipc/util.c
> index 503946e..faae296 100644
> --- a/ipc/util.c
> +++ b/ipc/util.c
> @@ -173,7 +173,7 @@ void __init ipc_init_proc_interface(const char *path, const char
> *header,
>   * @key: The key to find
>   *
>   * Requires ipc_ids.rw_mutex locked.
> - * Returns the LOCKED pointer to the ipc structure if found or NULL
> + * Returns the UNLOCKED pointer to the ipc structure if found or NULL
>   * if not.
>   * If key is found ipc points to the owning ipc structure
>   */
> @@ -195,7 +195,6 @@ static struct kern_ipc_perm *ipc_findkey(struct ipc_ids *ids, key_t key)
>   continue;
> }
>
> - ipc_lock_by_ptr(ipc);
>   return ipc;
> }
>
> @@ -203,6 +202,27 @@ static struct kern_ipc_perm *ipc_findkey(struct ipc_ids *ids, key_t key)
> }
>
> /**
> + * ipc_findkey_locked - find and lock a key in an ipc identifier set
> + * @ids: Identifier set
> + * @key: The key to find
> + *
> + * Requires ipc_ids.rw_mutex locked.
> + * Returns the LOCKED pointer to the ipc structure if found or NULL
> + * if not.
> + * If key is found ipc points to the owning ipc structure
> + */
> +
> +static struct kern_ipc_perm *ipc_findkey_locked(struct ipc_ids *ids, key_t key)
> +{
> + struct kern_ipc_perm *ipc;
> +
> + ipc = ipc_findkey(ids, key);
> + if (ipc)
> + ipc_lock_by_ptr(ipc);
> + return ipc;
> +}
> +
> +/**

```

```

> * ipc_get_maxid - get the last assigned id
> * @ids: IPC identifier set
> *
> @@ -388,7 +408,7 @@ retry:
>   * a new entry + read locks are not "upgradable"
>   */
>   down_write(&ids->rw_mutex);
> - ipcp = ipc_findkey(ids, params->key);
> + ipcp = ipc_findkey_locked(ids, params->key);
>   if (ipcp == NULL) {
>     /* key not used */
>     if (!(flg & IPC_CREAT))
> @@ -755,6 +775,31 @@ int ipcget(struct ipc_namespace *ns, struct ipc_ids *ids,
> }
>
> /**
> + * ipc_update_key - update the key of an IPC.
> + * @in: the permission given as input.
> + * @out: the permission of the ipc to set.
> +
> + * Common routine called by sys_shmctl(), sys_semctl(). sys_msgctl().
> +
> +int ipc_update_key(struct ipc_ids *ids, struct ipc64_perm *in,
> +    struct kern_ipc_perm *out)
> +{
> +
> + if (in->key && out->key != in->key) {
> + /*
> +  * Check for existent segment with the same key.
> +  * Note: ipc_ids.rw_mutex is taken for write already.
> + */
> + if (ipc_findkey(ids, in->key))
> + return -EXIST;
> +
> + out->cuid = in->cuid;
> + out->cgid = in->cgid;
> + out->key = in->key;
> + return 0;
> +
> +
> +/**
> + * ipc_update_perm - update the permissions of an IPC.
> + * @in: the permission given as input.
> + * @out: the permission of the ipc to set.
> diff --git a/ipc/util.h b/ipc/util.h
> index 3a9e558..271bded 100644
> --- a/ipc/util.h
> +++ b/ipc/util.h

```

```
> @@ -126,6 +126,8 @@ struct kern_ipc_perm *ipc_lock(struct ipc_ids *, int);
>
> void kernel_to_ipc64_perm(struct kern_ipc_perm *in, struct ipc64_perm *out);
> void ipc64_perm_to_ipc_perm(struct ipc64_perm *in, struct ipc_perm *out);
> +int ipc_update_key(struct ipc_ids *ids, struct ipc64_perm *in,
> +    struct kern_ipc_perm *out);
> int ipc_update_perm(struct ipc64_perm *in, struct kern_ipc_perm *out);
> struct kern_ipc_perm *ipcctl_pre_down(struct ipc_namespace *ns,
>     struct ipc_ids *ids, int id, int cmd,
>
> --
> To unsubscribe from this list: send the line "unsubscribe linux-security-module" in
> the body of a message to majordomo@vger.kernel.org
> More majordomo info at http://vger.kernel.org/majordomo-info.html
```

---