

---

Subject: Re: [PATCH 07/11] fuse: add per-page descriptor &lt;offset, length&gt; to fuse\_req (v2)

Posted by [Miklos Szteredi](#) on Thu, 25 Oct 2012 13:24:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Maxim Patlasov <[mpatlasov@parallels.com](mailto:mpatlasov@parallels.com)> writes:

```
> The ability to save page pointers along with lengths and offsets in fuse_req  
> will be useful to cover several iovec-s with a single fuse_req.  
>  
> Per-request page_offset is removed because anybody who need it can use  
> req->page_descs[0].offset instead.  
>  
> Changed in v2:  
> - replaced structure page_desc with fuse_page_desc  
>  
> Signed-off-by: Maxim Patlasov <mpatlasov@parallels.com>  
> ---  
> fs/fuse/dev.c | 26 ++++++-----  
> fs/fuse/file.c | 10 +----  
> fs/fuse/fuse_i.h | 15 +-----  
> 3 files changed, 36 insertions(+), 15 deletions(-)  
>  
> diff --git a/fs/fuse/dev.c b/fs/fuse/dev.c  
> index b241a7d..72ad962 100644  
> --- a/fs/fuse/dev.c  
> +++ b/fs/fuse/dev.c  
> @@ -35,14 +35,17 @@ static struct fuse_conn *fuse_get_conn(struct file *file)  
> }  
>  
> static void fuse_request_init(struct fuse_req *req, struct page **pages,  
> + struct fuse_page_desc *page_descs,  
> unsigned npages)  
> {  
>   memset(req, 0, sizeof(*req));  
> + memset(page_descs, 0, sizeof(*page_descs) * npages);
```

Makes me wonder: why aren't we zeroing out the page array too?

```
> INIT_LIST_HEAD(&req->list);  
> INIT_LIST_HEAD(&req->intr_entry);  
> init_waitqueue_head(&req->waitq);  
> atomic_set(&req->count, 1);  
> req->pages = pages;  
> + req->page_descs = page_descs;  
> req->max_pages = npages;  
> }  
>
```

```

> @@ -51,18 +54,25 @@ static struct fuse_req *__fuse_request_alloc(int npages, gfp_t flags)
>   struct fuse_req *req = kmem_cache_alloc(fuse_req_cachep, flags);
>   if (req) {
>     struct page **pages;
> +   struct fuse_page_desc *page_descs;
>
> -   if (npages <= FUSE_REQ_INLINE_PAGES)
> +   if (npages <= FUSE_REQ_INLINE_PAGES) {
>     pages = req->inline_pages;
> - else
> +   page_descs = req->inline_page_descs;
> + } else {
>     pages = kmalloc(sizeof(struct page *) * npages, flags);
> +   page_descs = kmalloc(sizeof(struct fuse_page_desc) *
> +     npages, flags);
> + }
>
> - if (!pages) {
> + if (!pages || !page_descs) {
> +   kfree(pages);
> +   kfree(page_descs);
>     kmem_cache_free(fuse_req_cachep, req);
>     return NULL;
>   }
>
> - fuse_request_init(req, pages, npages);
> + fuse_request_init(req, pages, page_descs, npages);
> }
> return req;
> }
> @@ -82,6 +92,8 @@ void fuse_request_free(struct fuse_req *req)
> {
>   if (req->pages != req->inline_pages)
>     kfree(req->pages);
> + if (req->page_descs != req->inline_page_descs)
> +   kfree(req->page_descs);

```

You allocate them together, you can free them together. Just add a BUG\_ON() if you feel paranoid.

```

>   kmem_cache_free(fuse_req_cachep, req);
> }
>
> @@ -186,7 +198,7 @@ static void put_reserved_req(struct fuse_conn *fc, struct fuse_req *req)
>   struct fuse_file *ff = file->private_data;
>
>   spin_lock(&fc->lock);
> - fuse_request_init(req, req->pages, req->max_pages);

```

```

> + fuse_request_init(req, req->pages, req->page_descs, req->max_pages);
> BUG_ON(ff->reserved_req);
> ff->reserved_req = req;
> wake_up_all(&fc->reserved_req_waitq);
> @@ -877,7 +889,7 @@ static int fuse_copy_pages(struct fuse_copy_state *cs, unsigned
nbytes,
> {
>     unsigned i;
>     struct fuse_req *req = cs->req;
> -    unsigned offset = req->page_offset;
> +    unsigned offset = req->page_descs[0].offset;
>     unsigned count = min(nbytes, (unsigned) PAGE_SIZE - offset);
>
>     for (i = 0; i < req->num_pages && (nbytes || zeroing); i++) {
> @@ -1585,7 +1597,7 @@ static int fuse_retrieve(struct fuse_conn *fc, struct inode *inode,
>     req->in.h.nodeid = outarg->nodeid;
>     req->in.numargs = 2;
>     req->in.argmax = 1;
> -    req->page_offset = offset;
> +    req->page_descs[0].offset = offset;
>     req->end = fuse_retrieve_end;
>
>     index = outarg->offset >> PAGE_CACHE_SHIFT;
> diff --git a/fs/fuse/file.c b/fs/fuse/file.c
> index 08899a6..b68cf3b 100644
> --- a/fs/fuse/file.c
> +++ b/fs/fuse/file.c
> @@ -798,7 +798,7 @@ static size_t fuse_send_write_pages(struct fuse_req *req, struct file
*file,
>
>     res = fuse_send_write(req, file, pos, count, NULL);
>
> -    offset = req->page_offset;
> +    offset = req->page_descs[0].offset;
>     count = res;
>     for (i = 0; i < req->num_pages; i++) {
>         struct page *page = req->pages[i];
> @@ -829,7 +829,7 @@ static ssize_t fuse_fill_write_pages(struct fuse_req *req,
>     int err;
>
>     req->in.argmax = 1;
> -    req->page_offset = offset;
> +    req->page_descs[0].offset = offset;
>
>     do {
>         size_t tmp;
> @@ -1070,14 +1070,14 @@ static int fuse_get_user_pages(struct fuse_req *req, const char
__user *buf,

```

```

>     return npages;
>
>     req->num_pages = npages;
> - req->page_offset = offset;
> + req->page_descs[0].offset = offset;
>
>     if (write)
>         req->in.argpages = 1;
>     else
>         req->out.argpages = 1;
>
> - nbytes = (req->num_pages << PAGE_SHIFT) - req->page_offset;
> + nbytes = (req->num_pages << PAGE_SHIFT) - req->page_descs[0].offset;
>     *nbytesp = min(*nbytesp, nbytes);
>
>     return 0;
> @@ -1314,7 +1314,7 @@ static int fuse_writepage_locked(struct page *page)
>     req->in.argpages = 1;
>     req->num_pages = 1;
>     req->pages[0] = tmp_page;
> - req->page_offset = 0;
> + req->page_descs[0].offset = 0;
>     req->end = fuse_writepage_end;
>     req->inode = inode;
>
> diff --git a/fs/fuse/fuse_i.h b/fs/fuse/fuse_i.h
> index fd69d62..c07e454 100644
> --- a/fs/fuse/fuse_i.h
> +++ b/fs/fuse/fuse_i.h
> @@ -203,6 +203,12 @@ struct fuse_out {
>     struct fuse_arg args[3];
> };
>
> +/** FUSE page descriptor */
> +struct fuse_page_desc {
> +    unsigned int length;
> +    unsigned int offset;
> +};
> +
> /** The request state */
> enum fuse_req_state {
>     FUSE_REQ_INIT = 0,
> @@ -296,18 +302,21 @@ struct fuse_req {
>     /** page vector */
>     struct page **pages;
>
> +    /** page-descriptor vector */
> +    struct fuse_page_desc *page_descs;

```

```
> +
> /** size of the 'pages' array */
> unsigned max_pages;
>
> /** inline page vector */
> struct page *inline_pages[FUSE_REQ_INLINE_PAGES];
>
> +/** inline page-descriptor vector */
> + struct fuse_page_desc inline_page_descs[FUSE_REQ_INLINE_PAGES];
> +
> /** number of pages in vector */
> unsigned num_pages;
>
> -/** offset of data on first page */
> - unsigned page_offset;
> -
> /** File used in the request (or NULL) */
> struct fuse_file *ff;
>
```

---