Subject: [PATCH 1/5] ipc: wrap new sysctls for CRIU inside CONFIG_CHECKPOINT_RESTORE
Posted by Stanislav Kinsbursky on Fri, 26 Oct 2012 11:05:57 GMT
View Forum Message <> Reply to Message

This patch set wraps "msg_next_id", "sem_next_id" and "shm_next_id" inside CONFIG_CHECKPOINT_RESTORE macro.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>
---
 ipc/ipc_sysctl.c | 4 ++++
 1 files changed, 4 insertions(+), 0 deletions(-)

```
diff --git a/ipc/ipc_sysctl.c b/ipc/ipc_sysctl.c
index d06d77a..130dfec 100644
--- a/ipc/ipc_sysctl.c
+++ b/ipc/ipc_sysctl.c
@@ -158,7 +158,9 @@ static int proc_ipcauto_dointvec_minmax(ctl_table *table, int write,

 static int zero;
 static int one = 1;
+#ifdef CONFIG_CHECKPOINT_RESTORE
 static int int_max = INT_MAX;
+#endif

 static struct ctl_table ipc_kern_table[] = {
  {
@@ -228,6 +230,7 @@ static struct ctl_table ipc_kern_table[] = {
   .extra1  = &zero,
   .extra2  = &one,
  },
+#ifdef CONFIG_CHECKPOINT_RESTORE
  {
   .procname = "sem_next_id",
   .data  = &init_ipc_ns.ids[IPC_SEM_IDS].next_id,
@@ -255,6 +258,7 @@ static struct ctl_table ipc_kern_table[] = {
   .extra1  = &zero,
   .extra2  = &int_max,
  },
+#endif
  {}
 };
```