
Subject: Fwd: [PATCH] pidspace is_init()
Posted by [Sukadev Bhattiprolu](#) on Tue, 01 Aug 2006 17:28:34 GMT
[View Forum Message](#) <> [Reply to Message](#)

CCing Vserver and OpenVz lists.

BTW, can we add these two lists to the lxc-devel list ?

----- Forwarded message from Sukadev Bhattiprolu <sukadev@us.ibm.com> -----

| Date: Tue, 1 Aug 2006 09:41:26 -0700
| From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
| To: Linux Containers on Source Forge <lxc-devel@lists.sourceforge.net>,
| ebiederm@xmission.com
| Cc: haveblue@us.ibm.com, clg@fr.ibm.com, serue@us.ibm.com,
| sukadev@us.ibm.com
| Subject: [PATCH] pidspace is_init()

| Eric,

| This is an updated version of your is_init() patch.
| (<http://lkml.org/lkml/2006/2/6/280>). It applies cleanly to 2.6.18-rc2
| and replaces a few more instances of ->pid == 1 with is_init().

| Further, is_init() checks pid (for now) and thus removes dependency on
| your other patches.

| Please review and let me know if I can send it out to LKML.

| Couple of questions:

| Are there cases where child_reaper is not pid = 1. Should the
| "tsk == child_reaper" check in do_exit() be replaced with is_init() ?

| Looks like, we would need a similar, is_idle() wrapper for "pid==0"
| checks - although the name is_idle_task() maybe more intuitive. If
| so, should we rename is_init() to is_init_task() ?

| Eric's original description:

| There are a lot of places in the kernel where we test for init
| because we give it special properties. Most significantly init
| must not die. This results in code all over the kernel test
| ->pid == 1.

| Introduce is_init to capture this case.

|

| With multiple pid spaces for all of the cases affected we are
| looking for only the first process on the system, not some other
| process that has pid == 1.

| Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>
| Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
| Cc: Dave Hansen <haveblue@us.ibm.com>
| Cc: Serge Hallyn <serue@us.ibm.com>
| Cc: Cedric Le Goater <clg@fr.ibm.com>
| Cc: lxc-devel@lists.sourceforge.net

| arch/alpha/mm/fault.c | 2 +-
| arch/arm/mm/fault.c | 2 +-
| arch/arm26/mm/fault.c | 2 +-
| arch/i386/lib/usercopy.c | 2 +-
| arch/i386/mm/fault.c | 2 +-
| arch/ia64/mm/fault.c | 2 +-
| arch/m32r/mm/fault.c | 2 +-
| arch/m68k/mm/fault.c | 2 +-
| arch/mips/mm/fault.c | 2 +-
| arch/powerpc/mm/fault.c | 2 +-
| arch/powerpc/platforms/pseries/ras.c | 2 +-
| arch/ppc/kernel/traps.c | 2 +-
| arch/ppc/mm/fault.c | 2 +-
| arch/s390/mm/fault.c | 2 +-
| arch/sh/mm/fault.c | 2 +-
| arch/sh64/mm/fault.c | 6 +++---
| arch/um/kernel/trap.c | 2 +-
| arch/x86_64/mm/fault.c | 4 +++--
| arch/xtensa/mm/fault.c | 2 +-
| drivers/char/sysrq.c | 2 +-
| include/linux/sched.h | 10 ++++++++
| kernel/capability.c | 2 +-
| kernel/cpuset.c | 2 +-
| kernel/exit.c | 2 +-
| kernel/kexec.c | 2 +-
| kernel/ptrace.c | 1 +
| kernel/sysctl.c | 2 +-
| mm/oom_kill.c | 6 +++---
| security/commoncap.c | 2 +-
| security/seclvl.c | 9 +++++---
| 30 files changed, 48 insertions(+), 36 deletions(-)

| Index: linux-2.6.18-rc2c/arch/alpha/mm/fault.c

| =====
| --- linux-2.6.18-rc2c.orig/arch/alpha/mm/fault.c 2006-07-28 09:20:03.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/alpha/mm/fault.c 2006-07-28 09:35:37.000000000 -0700

```

@@ -193,7 +193,7 @@ do_page_fault(unsigned long address, uns
/* We ran out of memory, or some other thing happened to us that
   made us unable to handle the page fault gracefully. */
out_of_memory:
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
Index: linux-2.6.18-rc2c/arch/arm/mm/fault.c
=====
--- linux-2.6.18-rc2c.orig/arch/arm/mm/fault.c 2006-07-28 09:20:04.000000000 -0700
+++ linux-2.6.18-rc2c/arch/arm/mm/fault.c 2006-07-31 17:53:40.000000000 -0700
@@ -197,7 +197,7 @@ survive:
    return fault;
}

- if (tsk->pid != 1)
+ if (!is_init(tsk))
    goto out;

/*
Index: linux-2.6.18-rc2c/arch/arm26/mm/fault.c
=====
--- linux-2.6.18-rc2c.orig/arch/arm26/mm/fault.c 2006-07-28 09:19:59.000000000 -0700
+++ linux-2.6.18-rc2c/arch/arm26/mm/fault.c 2006-07-31 22:48:32.000000000 -0700
@@ -185,7 +185,7 @@ survive:
}

    fault = -3; /* out of memory */
- if (tsk->pid != 1)
+ if (!is_init(tsk))
    goto out;

/*
Index: linux-2.6.18-rc2c/arch/i386/lib/usercopy.c
=====
--- linux-2.6.18-rc2c.orig/arch/i386/lib/usercopy.c 2006-07-28 09:19:49.000000000 -0700
+++ linux-2.6.18-rc2c/arch/i386/lib/usercopy.c 2006-07-28 09:35:37.000000000 -0700
@@ -739,7 +739,7 @@ survive:
    retval = get_user_pages(current, current->mm,
        (unsigned long)to, 1, 1, 0, &pg, NULL);

- if (retval == -ENOMEM && current->pid == 1) {
+ if (retval == -ENOMEM && is_init(current)) {
    up_read(&current->mm->mmap_sem);
    blk_congestion_wait(WRITE, HZ/50);
    goto survive;

```

```

| Index: linux-2.6.18-rc2c/arch/i386/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/i386/mm/fault.c 2006-07-28 09:19:49.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/i386/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -598,7 +598,7 @@ no_context:
| */
| out_of_memory:
| up_read(&mm->mmap_sem);
| - if (tsk->pid == 1) {
| + if (is_init(tsk)) {
|     yield();
|     down_read(&mm->mmap_sem);
|     goto survive;
| Index: linux-2.6.18-rc2c/arch/ia64/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/ia64/mm/fault.c 2006-07-28 09:20:02.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/ia64/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -278,7 +278,7 @@ ia64_do_page_fault (unsigned long addres
|
|     out_of_memory:
|     up_read(&mm->mmap_sem);
| - if (current->pid == 1) {
| + if (is_init(current)) {
|     yield();
|     down_read(&mm->mmap_sem);
|     goto survive;
| Index: linux-2.6.18-rc2c/arch/m32r/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/m32r/mm/fault.c 2006-07-28 09:20:09.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/m32r/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -299,7 +299,7 @@ no_context:
| */
| out_of_memory:
| up_read(&mm->mmap_sem);
| - if (tsk->pid == 1) {
| + if (is_init(tsk)) {
|     yield();
|     down_read(&mm->mmap_sem);
|     goto survive;
| Index: linux-2.6.18-rc2c/arch/m68k/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/m68k/mm/fault.c 2006-07-28 09:20:00.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/m68k/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -181,7 +181,7 @@ good_area:
| */
| out_of_memory:
| up_read(&mm->mmap_sem);
| - if (current->pid == 1) {

```

```

| + if (is_init(current)) {
|   yield();
|   down_read(&mm->mmap_sem);
|   goto survive;
| Index: linux-2.6.18-rc2c/arch/mips/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/mips/mm/fault.c 2006-07-28 09:19:54.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/mips/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -171,7 +171,7 @@ no_context:
|   */
|   out_of_memory:
|   up_read(&mm->mmap_sem);
| - if (tsk->pid == 1) {
| + if (is_init(tsk)) {
|   yield();
|   down_read(&mm->mmap_sem);
|   goto survive;
| Index: linux-2.6.18-rc2c/arch/powerpc/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/powerpc/mm/fault.c 2006-07-28 09:20:10.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/powerpc/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -386,7 +386,7 @@ bad_area_nosemaphore:
|   */
|   out_of_memory:
|   up_read(&mm->mmap_sem);
| - if (current->pid == 1) {
| + if (is_init(current)) {
|   yield();
|   down_read(&mm->mmap_sem);
|   goto survive;
| Index: linux-2.6.18-rc2c/arch/powerpc/platforms/pseries/ras.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/powerpc/platforms/pseries/ras.c 2006-07-28 09:20:10.000000000
-0700
| +++ linux-2.6.18-rc2c/arch/powerpc/platforms/pseries/ras.c 2006-07-28 09:35:37.000000000
-0700
| @@ -337,7 +337,7 @@ static int recover_mce(struct pt_regs *r
|   err->disposition == RTAS_DISP_NOT_RECOVERED &&
|   err->target == RTAS_TARGET_MEMORY &&
|   err->type == RTAS_TYPE_ECC_UNCORR &&
| -   !(current->pid == 0 || current->pid == 1)) {
| +   !(current->pid == 0 || is_init(current))) {
|   /* Kill off a user process with an ECC error */
|   printk(KERN_ERR "MCE: uncorrectable ecc error for pid %d\n",
|         current->pid);
| Index: linux-2.6.18-rc2c/arch/ppc/kernel/traps.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/ppc/kernel/traps.c 2006-07-28 09:19:52.000000000 -0700

```

```

| +++ linux-2.6.18-rc2c/arch/ppc/kernel/traps.c 2006-07-28 13:10:05.000000000 -0700
| @@ -119,7 +119,7 @@ void _exception(int signr, struct pt_reg
| * generate the same exception over and over again and we get
| * nowhere. Better to kill it and let the kernel panic.
| */
| - if (current->pid == 1) {
| + if (is_init(current)) {
|   __sighandler_t handler;
|
|   spin_lock_irq(&current->sigband->siglock);
| Index: linux-2.6.18-rc2c/arch/ppc/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/ppc/mm/fault.c 2006-07-28 09:19:51.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/ppc/mm/fault.c 2006-07-28 13:11:06.000000000 -0700
| @@ -291,7 +291,7 @@ bad_area:
| */
| out_of_memory:
| up_read(&mm->mmap_sem);
| - if (current->pid == 1) {
| + if (is_init(current)) {
|   yield();
|   down_read(&mm->mmap_sem);
|   goto survive;
| Index: linux-2.6.18-rc2c/arch/s390/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/s390/mm/fault.c 2006-07-28 09:20:08.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/s390/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -315,7 +315,7 @@ no_context:
| */
| out_of_memory:
| up_read(&mm->mmap_sem);
| - if (tsk->pid == 1) {
| + if (is_init(tsk)) {
|   yield();
|   goto survive;
| }
| Index: linux-2.6.18-rc2c/arch/sh/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/sh/mm/fault.c 2006-07-28 09:19:59.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/sh/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -160,7 +160,7 @@ no_context:
| */
| out_of_memory:
| up_read(&mm->mmap_sem);
| - if (current->pid == 1) {
| + if (is_init(current)) {
|   yield();
|   down_read(&mm->mmap_sem);

```

```

| goto survive;
| Index: linux-2.6.18-rc2c/arch/sh64/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/sh64/mm/fault.c 2006-07-28 09:20:08.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/sh64/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -277,7 +277,7 @@ bad_area:
|     show_regs(regs);
| #endif
| }
| - if (tsk->pid == 1) {
| + if (is_init(tsk)) {
|     panic("INIT had user mode bad_area\n");
| }
|     tsk->thread.address = address;
| @@ -319,14 +319,14 @@ no_context:
|     * us unable to handle the page fault gracefully.
|     */
| out_of_memory:
| - if (current->pid == 1) {
| + if (is_init(current)) {
|     panic("INIT out of memory\n");
|     yield();
|     goto survive;
| }
| printk("fault:Out of memory\n");
| up_read(&mm->mmap_sem);
| - if (current->pid == 1) {
| + if (is_init(current)) {
|     yield();
|     down_read(&mm->mmap_sem);
|     goto survive;
| Index: linux-2.6.18-rc2c/arch/um/kernel/trap.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/um/kernel/trap.c 2006-07-28 09:19:53.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/um/kernel/trap.c 2006-07-28 09:42:26.000000000 -0700
| @@ -120,7 +120,7 @@ out_nosemaphore:
|     * us unable to handle the page fault gracefully.
|     */
| out_of_memory:
| - if (current->pid == 1) {
| + if (is_init(current)) {
|     up_read(&mm->mmap_sem);
|     yield();
|     down_read(&mm->mmap_sem);
| Index: linux-2.6.18-rc2c/arch/x86_64/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/x86_64/mm/fault.c 2006-07-28 09:20:06.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/x86_64/mm/fault.c 2006-07-28 13:35:51.000000000 -0700

```

```

| @@ -250,7 +250,7 @@ static int is_errata93(struct pt_regs *r
|
| int unhandled_signal(struct task_struct *tsk, int sig)
| {
| - if (tsk->pid == 1)
| + if (is_init(tsk))
|     return 1;
|     if (tsk->ptrace & PT_PTRACED)
|         return 0;
| @@ -586,7 +586,7 @@ no_context:
|     */
| out_of_memory:
|     up_read(&mm->mmap_sem);
| - if (current->pid == 1) {
| + if (is_init(current)) {
|     yield();
|     goto again;
| }
| Index: linux-2.6.18-rc2c/arch/xtensa/mm/fault.c
| =====
| --- linux-2.6.18-rc2c.orig/arch/xtensa/mm/fault.c 2006-07-28 09:20:09.000000000 -0700
| +++ linux-2.6.18-rc2c/arch/xtensa/mm/fault.c 2006-07-28 09:35:37.000000000 -0700
| @@ -144,7 +144,7 @@ bad_area:
|     */
| out_of_memory:
|     up_read(&mm->mmap_sem);
| - if (current->pid == 1) {
| + if (is_init(current)) {
|     yield();
|     down_read(&mm->mmap_sem);
|     goto survive;
| Index: linux-2.6.18-rc2c/drivers/char/sysrq.c
| =====
| --- linux-2.6.18-rc2c.orig/drivers/char/sysrq.c 2006-07-28 09:19:35.000000000 -0700
| +++ linux-2.6.18-rc2c/drivers/char/sysrq.c 2006-07-31 17:54:38.000000000 -0700
| @@ -208,7 +208,7 @@ static void send_sig_all(int sig)
|     struct task_struct *p;
|
|     for_each_process(p) {
| - if (p->mm && p->pid != 1)
| + if (p->mm && !is_init(p))
|         /* Not swapper, init nor kernel thread */
|         force_sig(sig, p);
|     }
| Index: linux-2.6.18-rc2c/include/linux/sched.h
| =====
| --- linux-2.6.18-rc2c.orig/include/linux/sched.h 2006-07-28 09:20:13.000000000 -0700
| +++ linux-2.6.18-rc2c/include/linux/sched.h 2006-07-31 17:55:09.000000000 -0700

```

```
| @@ -1017,6 +1017,16 @@ static inline int pid_alive(struct task_
| return p->pids[PIDTYPE_PID].pid != NULL;
| }
|
| +/**
| + * is_init - check if a task structure is the first user space
| + * task the kernel created.
| + * @p: Task structure to be checked.
| + */
| +static inline int is_init(struct task_struct *tsk)
| +{
| + return tsk->pid == 1;
| +}
| +
| extern void free_task(struct task_struct *tsk);
| #define get_task_struct(tsk) do { atomic_inc(&(tsk)->usage); } while(0)
```

| Index: linux-2.6.18-rc2c/kernel/capability.c

```
| =====
| --- linux-2.6.18-rc2c.orig/kernel/capability.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/kernel/capability.c 2006-07-28 13:12:12.000000000 -0700
| @@ -133,7 +133,7 @@ static inline int cap_set_all(kernel_cap
| int found = 0;
|
| do_each_thread(g, target) {
| - if (target == current || target->pid == 1)
| + if (target == current || is_init(target))
| continue;
| found = 1;
| if (security_capset_check(target, effective, inheritable,
```

| Index: linux-2.6.18-rc2c/kernel/cpuset.c

```
| =====
| --- linux-2.6.18-rc2c.orig/kernel/cpuset.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/kernel/cpuset.c 2006-07-28 13:13:04.000000000 -0700
| @@ -240,7 +240,7 @@ static struct super_block *cpuset_sb;
| * A cpuset can only be deleted if both its 'count' of using tasks
| * is zero, and its list of 'children' cpusets is empty. Since all
| * tasks in the system use _some_ cpuset, and since there is always at
| - * least one task in the system (init, pid == 1), therefore, top_cpuset
| + * least one task in the system (init), therefore, top_cpuset
| * always has either children cpusets and/or using tasks. So we don't
| * need a special hack to ensure that top_cpuset cannot be deleted.
| *
```

| Index: linux-2.6.18-rc2c/kernel/exit.c

```
| =====
| --- linux-2.6.18-rc2c.orig/kernel/exit.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/kernel/exit.c 2006-07-31 17:58:58.000000000 -0700
| @@ -219,7 +219,7 @@ static int will_become_orphaned_pgrp(int
```

```

| do_each_task_pid(pgrp, PIDTYPE_PGID, p) {
|   if (p == ignored_task
|       || p->exit_state
-   || p->real_parent->pid == 1)
+   || is_init(p->real_parent))
|     continue;
|   if (process_group(p->real_parent) != pgrp
|       && p->real_parent->signal->session == p->signal->session) {
Index: linux-2.6.18-rc2c/kernel/kexec.c
| =====
| --- linux-2.6.18-rc2c.orig/kernel/kexec.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/kernel/kexec.c 2006-07-28 09:35:37.000000000 -0700
| @@ -40,7 +40,7 @@ struct resource crashk_res = {
|
| int kexec_should_crash(struct task_struct *p)
| {
- if (in_interrupt() || !p->pid || p->pid == 1 || panic_on_oops)
+ if (in_interrupt() || !p->pid || is_init(p) || panic_on_oops)
|   return 1;
|   return 0;
| }
Index: linux-2.6.18-rc2c/kernel/ptrace.c
| =====
| --- linux-2.6.18-rc2c.orig/kernel/ptrace.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/kernel/ptrace.c 2006-07-31 18:05:06.000000000 -0700
| @@ -494,6 +494,7 @@ struct task_struct *ptrace_get_task_stru
|   child = find_task_by_pid(pid);
|   if (child)
|     get_task_struct(child);
+
|   read_unlock(&tasklist_lock);
|   if (!child)
|     return ERR_PTR(-ESRCH);
Index: linux-2.6.18-rc2c/kernel/sysctl.c
| =====
| --- linux-2.6.18-rc2c.orig/kernel/sysctl.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/kernel/sysctl.c 2006-07-28 09:35:37.000000000 -0700
| @@ -1867,7 +1867,7 @@ int proc_dointvec_bset(ctl_table *table,
|   return -EPERM;
| }
|
- op = (current->pid == 1) ? OP_SET : OP_AND;
+ op = is_init(current) ? OP_SET : OP_AND;
|   return do_proc_dointvec(table, write, filp, buffer, lenp, ppos,
|       do_proc_dointvec_bset_conv, &op);
| }
Index: linux-2.6.18-rc2c/mm/oom_kill.c
| =====

```

```

| --- linux-2.6.18-rc2c.orig/mm/oom_kill.c 2006-07-28 09:20:50.000000000 -0700
| +++ linux-2.6.18-rc2c/mm/oom_kill.c 2006-07-28 09:35:37.000000000 -0700
| @@ -191,8 +191,8 @@ static struct task_struct *select_bad_pr
|   unsigned long points;
|   int releasing;
|
| - /* skip the init task with pid == 1 */
| - if (p->pid == 1)
| + /* skip the init task */
| + if (is_init(p))
|     continue;
|     if (p->oomkilladj == OOM_DISABLE)
|         continue;
| @@ -227,7 +227,7 @@ static struct task_struct *select_bad_pr
|   */
| static void __oom_kill_task(struct task_struct *p, const char *message)
| {
| - if (p->pid == 1) {
| + if (is_init(p)) {
|     WARN_ON(1);
|     printk(KERN_WARNING "tried to kill init!\n");
|     return;
| Index: linux-2.6.18-rc2c/security/commoncap.c
| =====
| --- linux-2.6.18-rc2c.orig/security/commoncap.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/security/commoncap.c 2006-07-31 18:05:35.000000000 -0700
| @@ -169,7 +169,7 @@ void cap_bprm_apply_creds (struct linux_
|   /* For init, we want to retain the capabilities set
|    * in the init_task struct. Thus we skip the usual
|    * capability rules */
| - if (current->pid != 1) {
| + if (!is_init(current)) {
|     current->cap_permitted = new_permitted;
|     current->cap_effective =
|         cap_intersect (new_permitted, bprm->cap_effective);
| Index: linux-2.6.18-rc2c/security/seclvl.c
| =====
| --- linux-2.6.18-rc2c.orig/security/seclvl.c 2006-07-28 09:20:49.000000000 -0700
| +++ linux-2.6.18-rc2c/security/seclvl.c 2006-07-31 18:06:33.000000000 -0700
| @@ -287,7 +287,7 @@ static struct file_operations passwd_fil
|   */
| static int seclvl_ptrace(struct task_struct *parent, struct task_struct *child)
| {
| - if (seclvl >= 0 && child->pid == 1) {
| + if (seclvl >= 0 && is_init(child)) {
|     seclvl_printk(1, KERN_WARNING, "Attempt to ptrace "
|         "the init process disallowed in "
|         "secure level %d\n", seclvl);

```

```

@@ -305,7 +305,7 @@ static int seclvl_capable(struct task_st
int rc = 0;

/* init can do anything it wants */
- if (tsk->pid == 1)
+ if (is_init(tsk))
return 0;

if (seclvl > 0) {
@@ -413,7 +413,8 @@ static void seclvl_bd_release(struct ino
static int
seclvl_inode_permission(struct inode *inode, int mask, struct nameidata *nd)
{
- if (current->pid != 1 && S_ISBLK(inode->i_mode) && (mask & MAY_WRITE)) {
+ if (!is_init(current)
+ && S_ISBLK(inode->i_mode) && (mask & MAY_WRITE)) {
switch (seclvl) {
case 2:
seclvl_printk(1, KERN_WARNING, "Write to block device "
@@ -465,7 +466,7 @@ static void seclvl_file_free_security(st
*/
static int seclvl_umount(struct vfsmount *mnt, int flags)
{
- if (current->pid != 1 && seclvl == 2) {
+ if (!is_init(current) && seclvl == 2) {
seclvl_printk(1, KERN_WARNING, "Attempt to unmount in secure "
"level %d\n", seclvl);
return -EPERM;

```

----- End forwarded message -----
