
Subject: Re: Problems with Gentoo template creation
Posted by [Ronald Tanner](#) on Fri, 11 Aug 2006 12:53:45 GMT
[View Forum Message](#) <> [Reply to Message](#)

My experiments show that setting the route with

```
/sbin/route add default dev venet0
```

on the VPS is sufficient.

```
localhost / # route -n
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
127.0.0.0 127.0.0.1 255.0.0.0 UG 0 0 0 lo
0.0.0.0 0.0.0.0 0.0.0.0 U 0 0 0 venet0
```

But if you have the line

```
OSTEMPLATE=gentoo-something
```

in your config file (eg. /etc/vz/777.conf) the routes are added automatically when you set up the ip address. However they look different:

```
localhost / # route -n
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
191.255.255.0 0.0.0.0 255.255.255.0 U 0 0 0 venet0
127.0.0.0 127.0.0.1 255.0.0.0 UG 0 0 0 lo
0.0.0.0 191.255.255.1 0.0.0.0 UG 0 0 0 venet0
```

for me these routes are somehow strange.

And there is another step in the preparation of the os template which needs some explanation. Why do I have to replace /etc/mstab with a link to /proc/mounts?

Regards
Ronald
