
Subject: Re: Using PPP in a Virtual Server
Posted by [eroux](#) on Thu, 17 Aug 2006 11:19:32 GMT
[View Forum Message](#) <> [Reply to Message](#)

From /var/log/messages on the VE:

```
Aug 17 13:09:14 vs01-vc01 pppd[17435]: pppd 2.4.3 started by root, uid 0
Aug 17 13:09:14 vs01-vc01 pppd[17435]: Couldn't create new ppp unit: Operation not permitted
Aug 17 13:09:14 vs01-vc01 pppd[17435]: Exit.
```

Here's the strace dump, though I'm not too sure what I'm to look for:

```
execve("/usr/sbin/pppd.org", ["/usr/sbin/pppd.org"], [/* 17 vars */]) = 0
brk(0) = 0x81c5000
uname({sys="Linux", node="vs01-vc01.vodacom.co.za", ...}) = 0
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=9024, ...}) = 0
mmap2(NULL, 9024, PROT_READ, MAP_PRIVATE, 3, 0) = 0xb7f39000
close(3) = 0
open("/lib/libutil.so.1", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260f\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=13388, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0xb7f38000
mmap2(NULL, 12432, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x497000
mmap2(0x499000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1) = 0x499000
close(3) = 0
open("/lib/libcrypt.so.1", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\300\7\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=25928, ...}) = 0
mmap2(NULL, 184636, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x1d6000
mmap2(0x1db000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x4) = 0x1db000
mmap2(0x1dd000, 155964, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x1dd000
close(3) = 0
open("/lib/libpam.so.0", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\220\37"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=48056, ...}) = 0
mmap2(NULL, 50956, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0xd7c000
mmap2(0xd88000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xb) = 0xd88000
close(3) = 0
```

```

open("/lib/libdl.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0@\f\0\000"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=14612, ...}) = 0
mmap2(NULL, 12412, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x12c000
mmap2(0x12e000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1) = 0x12e000
close(3) = 0
open("/usr/lib/libpcap.so.0.9.4", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\3008\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=167092, ...}) = 0
mmap2(NULL, 167888, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x4af000
mmap2(0x4d7000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x28) = 0x4d7000
close(3) = 0
open("/lib/libc.so.6", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0JX\1\000"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1529400, ...}) = 0
mmap2(NULL, 1254780, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x204000
mmap2(0x331000, 12288, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x12d) = 0x331000
mmap2(0x334000, 9596, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x334000
close(3) = 0
open("/lib/libaudit.so.0", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0000\31\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=62908, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f37000
mmap2(NULL, 65800, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0xde3000
mmap2(0xdf2000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0xe) = 0xdf2000
close(3) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f36000
set_thread_area({entry_number:-1 -> 6, base_addr:0xb7f366c0, limit:1048575, seg_32bit:1,
contents:0, read_exec_only:0, limit_in_pages:1, seg_not_present:0, useable:1}) = 0
mprotect(0x331000, 8192, PROT_READ) = 0
mprotect(0x12e000, 4096, PROT_READ) = 0
mprotect(0x1db000, 4096, PROT_READ) = 0
mprotect(0x499000, 4096, PROT_READ) = 0
mprotect(0x12a000, 4096, PROT_READ) = 0
munmap(0xb7f39000, 9024) = 0
socket(PF_FILE, SOCK_DGRAM, 0) = 3
fcntl64(3, F_SETFD, FD_CLOEXEC) = 0

```

```

connect(3, {sa_family=AF_FILE, path="/dev/log"}, 110) = 0
uname({sys="Linux", node="vs01-vc01.vodacom.co.za", ...}) = 0
umask(0777) = 022
umask(022) = 0777
getuid32() = 0
brk(0) = 0x81c5000
brk(0x81e6000) = 0x81e6000
getgroups32(65536, [0, 1, 2, 3, 4, 6, 10]) = 7
gettimeofday({1155813160, 805264}, NULL) = 0
getpid() = 17529
open("/etc/ppp/options", O_RDONLY) = 4
fstat64(4, {st_mode=S_IFREG|0644, st_size=5, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f3b000
read(4, "lock\n", 4096) = 5
read(4, "", 4096) = 0
close(4) = 0
munmap(0xb7f3b000, 4096) = 0
getuid32() = 0
socket(PF_FILE, SOCK_STREAM, 0) = 4
fcntl64(4, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(4, F_SETFL, O_RDWR|O_NONBLOCK) = 0
connect(4, {sa_family=AF_FILE, path="/var/run/nscd/socket"}, 110) = -1 ENOENT (No such file or
directory)
close(4) = 0
socket(PF_FILE, SOCK_STREAM, 0) = 4
fcntl64(4, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(4, F_SETFL, O_RDWR|O_NONBLOCK) = 0
connect(4, {sa_family=AF_FILE, path="/var/run/nscd/socket"}, 110) = -1 ENOENT (No such file or
directory)
close(4) = 0
open("/etc/nsswitch.conf", O_RDONLY) = 4
fstat64(4, {st_mode=S_IFREG|0644, st_size=1696, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f3b000
read(4, "#\n# /etc/nsswitch.conf\n#\n# An ex"..., 4096) = 1696
read(4, "", 4096) = 0
close(4) = 0
munmap(0xb7f3b000, 4096) = 0
open("/etc/ld.so.cache", O_RDONLY) = 4
fstat64(4, {st_mode=S_IFREG|0644, st_size=9024, ...}) = 0
mmap2(NULL, 9024, PROT_READ, MAP_PRIVATE, 4, 0) = 0xb7f39000
close(4) = 0
open("/lib/libnss_files.so.2", O_RDONLY) = 4
read(4, "\177ELF1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0 \33\0\000"..., 512) = 512
fstat64(4, {st_mode=S_IFREG|0755, st_size=46608, ...}) = 0
mmap2(NULL, 41616, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 4, 0) =
0x99c000

```

```

mmap2(0x9a5000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 4, 0x8) = 0x9a5000
close(4) = 0
mprotect(0x9a5000, 4096, PROT_READ) = 0
munmap(0xb7f39000, 9024) = 0
open("/etc/passwd", O_RDONLY) = 4
fcntl64(4, F_GETFD) = 0
fcntl64(4, F_SETFD, FD_CLOEXEC) = 0
fstat64(4, {st_mode=S_IFREG|0644, st_size=805, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f3b000
read(4, "root:x:0:0:root:/root:/bin/bash\n"..., 4096) = 805
close(4) = 0
munmap(0xb7f3b000, 4096) = 0
getuid32() = 0
setresuid32(-1, 0, -1) = 0
open("/root/.ppprc", O_RDONLY) = -1 ENOENT (No such file or directory)
setresuid32(-1, 0, -1) = 0
ioctl(0, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
ioctl(0, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
readlink("/proc/self/fd/0", "/dev/pts/0", 4095) = 10
stat64("/dev/pts/0", {st_mode=S_IFCHR|0600, st_rdev=makedev(136, 0), ...}) = 0
open("/etc/ppp/options.pts.0", O_RDONLY) = -1 ENOENT (No such file or directory)
geteuid32() = 0
uname({sys="Linux", node="vs01-vc01.vodacom.co.za", ...}) = 0
open("/dev/ppp", O_RDWR) = 4
close(4) = 0
open("/etc/mstab", O_RDONLY) = 4
fstat64(4, {st_mode=S_IFREG|0444, st_size=0, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f3b000
read(4, "simfs / simfs rw 0 0\nproc /proc "..., 1024) = 74
close(4) = 0
munmap(0xb7f3b000, 4096) = 0
open("/proc/net/route", O_RDONLY) = 4
fstat64(4, {st_mode=S_IFREG|0444, st_size=0, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f3b000
read(4, "Iface\tDestination\tGateway \tFlags"..., 1024) = 512
close(4) = 0
munmap(0xb7f3b000, 4096) = 0
gettimeofday({1155813160, 811316}, NULL) = 0
open("/etc/resolv.conf", O_RDONLY) = 4
fstat64(4, {st_mode=S_IFREG|0644, st_size=81, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0xb7f3b000
read(4, "search vodacom.co.za vodacom.cor"..., 4096) = 81
read(4, "", 4096) = 0

```



```
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=632, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=632, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_WRLCK, whence=SEEK_SET, start=696, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_UNLCK, whence=SEEK_SET, start=696, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=304, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=304, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_WRLCK, whence=SEEK_SET, start=816, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_UNLCK, whence=SEEK_SET, start=816, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
rt_sigaction(SIGHUP, {0xc394e0, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGINT, {0xc39460, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGTERM, {0xc39460, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGCHLD, {0xc39410, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGUSR1, {0xc38b30, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGUSR2, {0xc393c0, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGABRT, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGALRM, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGFPE, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGILL, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGPIPE, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
```

```

rt_sigaction(SIGQUIT, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGSEGV, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGBUS, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGIO, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGPROF, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGSYS, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGTRAP, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGVTALRM, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER,
0x22c0f8}, NULL, 8) = 0
rt_sigaction(SIGXCPU, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGXFSZ, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER, 0x22c0f8},
NULL, 8) = 0
rt_sigaction(SIGPIPE, {SIG_IGN}, {0xc39330, [HUP INT USR2 TERM CHLD], SA_RESTORER,
0x22c0f8}, 8) = 0
gettimeofday({1155813160, 822670}, NULL) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
open("/dev/pts/0", O_RDWR|O_NONBLOCK) = 7
fcntl64(7, F_GETFL) = 0x802 (flags O_RDWR|O_NONBLOCK)
fcntl64(7, F_SETFL, O_RDWR) = 0
ioctl(7, TIOCMBIS, [TIOCM_DTR]) = -1 EINVAL (Invalid argument)
ioctl(7, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
ioctl(7, SNDCTL_TMR_CONTINUE or TCSETS, {B38400 -opost -isig -icanon -echo ...}) = 0
open("/dev/pts/0", O_RDWR) = 8
close(8) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_WRLCK, whence=SEEK_SET, start=952, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_UNLCK, whence=SEEK_SET, start=952, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
ioctl(7, TIOCEXCL, 0) = 0
ioctl(7, TIOCSETD, [3]) = 0
ioctl(7, PPPIOCGCHAN, 0xc7d5c4) = 0

```



```

open("/dev/ppp", O_RDWR) = 8
fcntl64(8, F_SETFD, FD_CLOEXEC) = 0
ioctl(8, PPPIOCATTCHAN, 0xc7d5c4) = 0
fcntl64(8, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(8, F_SETFL, O_RDWR|O_NONBLOCK) = 0
open("/dev/ppp", O_RDWR) = 9
fcntl64(9, F_GETFL) = 0x2 (flags O_RDWR)
fcntl64(9, F_SETFL, O_RDWR|O_NONBLOCK) = 0
ioctl(9, PPPIOCNEWUNIT, 0xcbfc28) = -1 EPERM (Operation not permitted)
time(NULL) = 1155813160
stat64("/etc/localtime", {st_mode=S_IFREG|0644, st_size=98, ...}) = 0
stat64("/etc/localtime", {st_mode=S_IFREG|0644, st_size=98, ...}) = 0
stat64("/etc/localtime", {st_mode=S_IFREG|0644, st_size=98, ...}) = 0
send(3, "<27>Aug 17 13:12:40 pppd[17529]:"..., 86, MSG_NOSIGNAL) = 86
close(8) = 0
ioctl(7, TIOCSETD, [0]) = 0
ioctl(7, SNDCTL_TMR_CONTINUE or TCSETSIF, {B38400 opost isig icanon echo ...}) = 0
close(7) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_WRLCK, whence=SEEK_SET, start=952, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_UNLCK, whence=SEEK_SET, start=952, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=472, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=632, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_WRLCK, whence=SEEK_SET, start=760, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_UNLCK, whence=SEEK_SET, start=760, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=632, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=304, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_WRLCK, whence=SEEK_SET, start=900, len=1}) = 0
fcntl64(6, F_SETLK, {type=F_UNLCK, whence=SEEK_SET, start=900, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_WRLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=164, len=1}) = 0
fcntl64(6, F_SETLKW, {type=F_UNLCK, whence=SEEK_SET, start=304, len=1}) = 0
time(NULL) = 1155813160
stat64("/etc/localtime", {st_mode=S_IFREG|0644, st_size=98, ...}) = 0
stat64("/etc/localtime", {st_mode=S_IFREG|0644, st_size=98, ...}) = 0
stat64("/etc/localtime", {st_mode=S_IFREG|0644, st_size=98, ...}) = 0
send(3, "<30>Aug 17 13:12:40 pppd[17529]:"..., 38, MSG_NOSIGNAL) = 38
exit_group(1) = ?

```

Regards,
Eugène