
Subject: Re: Add second HDD Custom Location / Partition

Posted by [vaverin](#) on Sat, 23 Jun 2018 05:33:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

[https://docs.virtuozzo.com/virtuozzo_7_command_line_referenc
e/managing-virtual-machines/prctlvm.html#managing-virtual-d evices](https://docs.virtuozzo.com/virtuozzo_7_command_line_reference/managing-virtual-machines/prctlvm.html#managing-virtual-d-evices)

```
prctl set <VM_name> [--device-add hdd | --device-set hdd<N>]
    [--image <file>] [--size <size>] [--iface <ide|scsi|virtio>]
    [--subtype <virtio-scsi|hyperv>] [--position <pos>]
    [--enable|--disable]
```

--device-set hdd<N> Modifies the parameters of an existing virtual hard disk.

Virtual hard disks are named using the hdd<N> format where <N> is the drive index number starting from 0 (e.g., hdd0, hdd1). To obtain the list of disk names, use the prctl list command with the --info option.

--image <file>

Specifies an image file that will be used to emulate the virtual disk.

If the specified image does not exist, it is created and used to emulate the virtual hard disk.

If the specified image exists, it is used to emulate the virtual hard disk.
