
Subject: *SOLVED* Q: Postfix Kills Interface of VirtualHost .. Install Hints?

Posted by [tchipman](#) on Fri, 25 Aug 2006 15:57:36 GMT

[View Forum Message](#) <> [Reply to Message](#)

I wanted to ask if anyone has hints about how to install Postfix such that grief doesn't ensue.

Currently, my config / issue is thus:

- CentOS 4.3 32-bit Hardware host platform
- Latest OpenVZ Stable kernel installed, running
- CentOS "Default" 32-bit (or "minimal") Virtual Host Environment

If I create a clean virtual machine, then install postfix and use "system-switch-mail" to disable sendmail / enable postfix..

Postfix seems to be having trouble because in the config is an option which specifies what interface to listen on. By default it is "localhost". I've tried changing it to

```
lo
venet0
venet0:0
```

and also tried adding entries to /etc/hosts for the above .. to reduce complaint from postfix when I do a "service postfix stop ; service postfix start" in the VZHost.

Alas, I get interesting results:

- (1) Postfix is pissed off
- (2) My interface falls off the map, ie:

BEFORE postfix is running:

---paste---

```
root@nema log]# ifconfig -a
```

```
lo      Link encap:Local Loopback
        inet addr:127.0.0.1  Mask:255.0.0.0
        UP LOOPBACK RUNNING  MTU:16436  Metric:1
        RX packets:28 errors:0 dropped:0 overruns:0 frame:0
        TX packets:28 errors:0 dropped:0 overruns:0 carrier:0
        collisions:0 txqueuelen:0
        RX bytes:3344 (3.2 KiB)  TX bytes:3344 (3.2 KiB)
```

```
venet0  Link encap:UNSPEC  HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
        inet addr:127.0.0.1  P-t-P:127.0.0.1  Bcast:0.0.0.0  Mask:255.255.255.255
        UP BROADCAST POINTOPOINT RUNNING NOARP  MTU:1500  Metric:1
        RX packets:488 errors:0 dropped:0 overruns:0 frame:0
        TX packets:287 errors:0 dropped:0 overruns:0 carrier:0
        collisions:0 txqueuelen:0
```

RX bytes:36797 (35.9 KiB) TX bytes:41549 (40.5 KiB)

```
venet0:0 Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
  inet addr:1X9.1X3.X3.2X9 P-t-P:1X9.1X3.X3.2X9 Bcast:1X9.1X3.X3.2X9
Mask:255.255.255.255
  UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
```

--end-paste--

(note "X" is added to make my IP private here in the posting, it is a regular number "for real"...

AFTER postfix is running:

--paste---

```
[root@hydra cache]# vzctl enter 239
```

```
entered into VPS 239
```

```
-bash-3.00# ifconfig -a
```

```
lo      Link encap:Local Loopback
  UP LOOPBACK RUNNING MTU:16436 Metric:1
  RX packets:28 errors:0 dropped:0 overruns:0 frame:0
  TX packets:28 errors:0 dropped:0 overruns:0 carrier:0
  collisions:0 txqueuelen:0
  RX bytes:3344 (3.2 KiB) TX bytes:3344 (3.2 KiB)
```

```
venet0  Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
  UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
  RX packets:4 errors:0 dropped:0 overruns:0 frame:0
  TX packets:3 errors:0 dropped:0 overruns:0 carrier:0
  collisions:0 txqueuelen:0
  RX bytes:216 (216.0 b) TX bytes:164 (164.0 b)
```

```
venet0:0 Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
  UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
```

```
-bash-3.00#
```

ie, no IP associated for venet0:0.

Ugh!

It strikes me as particularly interesting that postfix not only chokes, but kills the interface as well.

If anyone has comments on this, it would be greatly appreciated.

Many thanks,

--Tim
