
Subject: Re: [ckrm-tech] [PATCH] BC: resource beancounters (v4) (added user memory)

Posted by [Chandra Seetharaman](#) on Thu, 07 Sep 2006 19:29:15 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Thu, 2006-09-07 at 11:29 +0400, Pavel Emelianov wrote:

<snip>

> >> BUT: I remind you the talks at OKS/OLS and in previous UBC discussions.

> >> It was noted that having a separate interfaces for CPU, I/O bandwidth

> >>

> >

> > But, it will be lot simpler for the user to configure/use if they are

> > together. We should discuss this also.

> >

> IMHO such unification may only imply that one syscall is used to pass

> configuration info into kernel.

> Each controller has specific configuring parameters different from the

> other ones. E.g. CPU controller must assign a "weight" to each group to

> share CPU time accordingly, but what is a "weight" for memory controller?

> IO may operate on "bandwidth" and it's not clear what is a "bandwidth" in

> Kb/sec for CPU controller and so on.

CKRM/RG handles this by eliminating the units from the interface and abstracting them to be "shares". Each resource controller converts the shares to its own units and handles properly.

User can specify the quantities simply as a percentage. CPU controller would treat it as cycles/ticks (within a time), memory controller would treat it as number of pages, and I/O controller would treat it as bandwidth, and so on...

<snip>

--

Chandra Seetharaman | Be careful what you choose....
- sekharan@us.ibm.com |you may get it.
