
Subject: Re: startup scripts, network setup

Posted by [Vasily Tarasov](#) on Tue, 19 Sep 2006 13:19:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

Quote:I don't think I have the experience to make an insightful suggestion, but I'd be happy with a `_HOST` postfix after the existing option names, like `ADD_IP_HOST=debian_add_ip_host.sh`, `POST_CREATE_HOST=debian_postcreate_host.sh`, etc...

AFAIK there will be only one file like `<veid>.start` but it will be ran on HN. Something `<veid>.host-start...`

Quote:Do all partially matching `.conf` files get loaded, (`debian.conf` and `debian-3.1.conf` in my case) or best match only?

The rule is the following:

Suppose name of template is "debian-3.1"

If file `debian-3.1.conf` exists it will be loaded, no other files will be processed. But if `debian-3.1.conf` doesn't exist, then otemplate name "debian-3.1" will be truncated till first occurrence of "-" from the end. From "debian-3.1" we have "debian", thus `debian.conf` file will be loaded. If `debian.conf` doesn't exist default file will be loaded.

Quote:

Is there a list of all possible parameter names for the `VEID.conf` and the `dist/distname.conf` files somewhere, btw? And could I theoretically duplicate entries between them, and if yes, which overrides the other?

`man vps.conf` gives the list.

`dist/distname.conf` and `vps.conf` have different parameters. So no duplicating, overriding is possible.

HTH,
vass.

HTH,
vass.
