
Subject: Re: startup scripts, network setup

Posted by [Vasily Tarasov](#) on Tue, 19 Sep 2006 13:19:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

Quote:I don't think I have the experience to make an insightful suggestion, but I'd be happy with a _HOST postfix after the existing option names, like ADD_IP_HOST=debian_add_ip_host.sh, POST_CREATE_HOST=debian_postcreate_host.sh, etc...

AFAIK there will be only one file like <veid>.start but it will be ran on HN. Something <veid>.host-start...

Quote:Do all partially matching .conf files get loaded, (debian.conf and debian-3.1.conf in my case) or best match only?

The rule is the following:

Suppose name of template is "debian-3.1"

If file debian-3.1.conf exists it will be loaded, no other files will be processed. But if debian-3.1.conf doesn't exist, then otemplate name "debian-3.1" will be truncated till first occurance of "-" from the end. From "debian-3.1" we have "debian", thus debian.conf file will be loaded. If debian.conf doesn't exist default file will be loaded.

Quote:

Is there a list of all possible parameter names for the VEID.conf and the dist/distname.conf files somewhere, btw? And could I theoretically duplicate entries between them, and if yes, which overrides the other?

man vps.conf gives the list.

dist/distname.conf and vps.conf have different parameters. So no duplicating, overriding is possible.

HTH,
vass.

HTH,
vass.
