
Subject: 64bit DMA in i2o_block
Posted by [vaverin](#) on Fri, 22 Sep 2006 09:10:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

Markus,

I've found that your driver does not work correctly with following options:

```
CONFIG_I2O_EXT_ADAPTEC=y  
# CONFIG_I2O_EXT_ADAPTEC_DMA64 is not set
```

I've checked it on 2.6.18 kernel on x86_64 node with 4Gb memory.

I would note that I've not noticed any bugs on x86 kernels, but x86_64 does not work at all.

The behaviors of x86_64 kernels can differ:
sometimes driver can not find partition table:
i2o/hda: unknown partition table

sometimes it find not all partition:
i2o/hda: i2o/hda1 i2o/hda2 i2o/hda3 i2o/hda4 < >

in other cases it detects devices well but corrupt the memory and filesystem:

```
Sep 21 16:46:09 ts10 block-osm: registered device at major 80  
Sep 21 16:46:09 ts10 i2o/hda: i2o/hda1 i2o/hda2 i2o/hda3 i2o/hda4 < i2o/hda5 >  
Sep 21 16:46:09 ts10 block-osm: device added (TID: 207): i2o/hda  
Sep 21 16:46:09 ts10 kjournald starting. Commit interval 5 seconds  
Sep 21 16:46:09 ts10 EXT3-fs: mounted filesystem with ordered data mode.  
Sep 21 16:46:10 ts10 Freeing unused kernel memory: 236k freed  
Sep 21 16:46:10 ts10 hotplug[961]: segfault at 0000000000000008 rip  
00000032411088cf rsp 00007fff5b189050 error 4
```

When I enabled CONFIG_I2O_EXT_ADAPTEC_DMA64 -- all the troubles went away.

I've tried to investigate this issue, but I've not found and documentation described format of Adaptec's private messages.

I would like to ask you, is this behavior specific for my hardware (Adaptec ASR-2010S I2O Zero Channel)? If not, I believe it makes sense to enable CONFIG_I2O_EXT_ADAPTEC_DMA64 in Kconfig by default for 64-bit kernels.

Thank you,
Vasily Averin
