
Subject: Re: Add veid argument to vznetcfg
Posted by [kfh](#) on Fri, 06 Oct 2006 12:50:59 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Friday den 6. October 2006 14:45, Igor Sukhiih wrote:

```
> > Hi list,  
> >  
> > As I need the VEID number when bringing up veth interface,  
> > I changed init to VEID.  
> > (I have a vlan and bridge for each VE)  
> >  
> > vznetcfg init veth <dev>  
> > vznetcfg <veid> veth <dev>  
> >  
> > Best regards,  
  
> > Segtel A/S  
> >  
> > -----  
> >  
> > --- a/src/lib/veth.c 2006-10-06 13:09:00.268275416 +0200  
> > +++ b/src/lib/veth.c 2006-10-06 13:10:50.765528528 +0200  
> > @@ -93,7 +92,9 @@  
> > static int run_vznetcfg(envid_t veid, veth_dev *dev)  
> > {  
> >     int ret;  
> >     - char *argv[] = {VZNETCFG, "init", "veth", NULL, NULL};  
> >     + char veidstr[12];  
> >     + sprintf(veidstr, "%d", veid);  
> >     + char *argv[] = {VZNETCFG, veidstr, "veth", NULL, NULL};  
> >  
> >     if (stat_file(VZNETCFG) != 1)  
> >         return 0;  
> >  
>  
> Is it Ok for you if I'll pass it in the environment  
> VEID=xxx  
> --  
>   Igor.
```

Yes, feel free.

Regards,
Kristian.
