

---

Posted by [sitnikov](#) on Fri, 10 Nov 2006 12:18:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

```
[root@demo1 vz-scripts]# cat mysql_mount
```

```
#!/bin/sh
```

```
MODE=${0##*\.}
```

```
SRC=/vz/root/10002/var/lib/mysql
```

```
DST=/vz/root/10003/var/lib/mysql
```

```
MOUNTED=$(grep $DST /proc/mounts | wc -l)
```

```
mnt() {  
    if [ $MOUNTED -lt 1 ] && [ -d $DST ]; then  
        mount --bind $SRC $DST >/dev/null 2>&1  
    fi  
}
```

```
umnt() {  
    if [ $MOUNTED -gt 0 ]; then  
        umount $DST >/dev/null 2>&1  
    fi  
}
```

```
case "$MODE" in
```

```
    mount)
```

```
        mnt
```

```
        ;;
```

```
    umount)
```

```
        umnt
```

```
        ;;
```

```
    *)
```

```
        echo "Unknown mode ($MODE)"
```

```
        exit -1
```

```
        ;;
```

```
esac
```

```
[root@demo1 vz-scripts]# ls -la 1000[23].*mount
```

```
lrwxrwxrwx 1 root root 11 Nov 10 07:07 10002.mount -> mysql_mount
```

```
lrwxrwxrwx 1 root root 11 Nov 10 07:07 10002.umount -> mysql_mount
```

```
lrwxrwxrwx 1 root root 11 Nov 10 07:07 10003.mount -> mysql_mount  
lrwxrwxrwx 1 root root 11 Nov 10 07:07 10003.umount -> mysql_mount
```

---