
Subject: openvz initscript for gentoo
Posted by [kir](#) on Tue, 21 Nov 2006 23:10:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

I had problems using OpenVZ on my Gentoo notebook. Each time I (or ifplugd) stop or restart networking, OpenVZ stops. I think it is not what we want.

The problem is initscript contains "need net". In fact OpenVZ should work fine without networking.

While looking at the bug, I found another one -- OpenVZ modules should be loaded after iptables, not before! Perhaps this bug was invisible since iptables start before networking, and 'need net' statement was preferred to 'before iptables' statement.

The below patch is a solution to both problems. Note that iptables is not mentioned since iptables initscript itself has 'before net' so the proper order is maintained.

Please review.

```
diff --git a/etc/init.d/vz-gentoo b/etc/init.d/vz-gentoo
index ae332c4..46e840f 100644
--- a/etc/init.d/vz-gentoo
+++ b/etc/init.d/vz-gentoo
@@ -4,8 +4,7 @@ # Distributed under the terms of the GNU
# $Header:
# /var/www/viewcvs.gentoo.org/raw_cvs/gentoo-x86/sys-cluster/v zctl/files/vz-3.0.10.initd,v
1.2 2006/07/09 10:29:24 phreak Exp $
```

```
depend() {
-   need net
-   before iptables
+   after net
}
```

```
check_config() {
```
