
Subject: Some VE on one HW node cannot communicate each other (getting Time to live exceeded)

Posted by [Jan Tomasek](#) on Fri, 22 Dec 2006 09:19:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

I've server with two network cards in following setup:

```
auto eth0
iface eth0 inet static
    address 195.113.233.254
    netmask 255.255.255.0
    network 195.113.233.0
    broadcast 195.113.233.255
    gateway 195.113.233.1
```

```
auto eth0:0
iface eth0:0 inet static
    address 192.168.1.1
    netmask 255.255.255.0
    network 192.168.1.255
    broadcast 192.168.1.255
```

```
auto eth1
iface eth1 inet static
    address 195.113.187.37
    netmask 255.255.255.192
    network 195.113.187.0
    broadcast 195.113.187.63
    post-up ip rule add from 195.113.187.33 table 6
    post-up ip rule add from 195.113.187.35 table 6
    post-up ip route add default dev eth1 via 195.113.187.1 table 6
    post-down ip rule delete from 195.113.187.33 table 6
    post-down ip rule delete from 195.113.187.35 table 6
```

There are three networks on:

- 1) eth0 195.113.233.0/24 primary public network for OpenVZ systems
- 2) eth0:0 192.168.1.0/24 private network for system which should not waste publicaly routable IP but still need to be online
- 3) eth1 195.113.187.0/26 is secondary public network - I was using this range for physical systems which I'm now moving to VE

Everything is working fine, except communication between systems using eth1 and eth0.

Routing tables on HW node:

```
chlivek:~# ip rule
0:    from all lookup 255
32764: from 195.113.187.35 lookup 6
32765: from 195.113.187.33 lookup 6
32766: from all lookup main
32767: from all lookup default

chlivek:~# ip route
195.113.187.33 dev venet0 scope link src 192.168.1.1
192.168.1.2 dev venet0 scope link src 192.168.1.1
195.113.233.253 dev venet0 scope link src 192.168.1.1
195.113.233.252 dev venet0 scope link src 192.168.1.1
195.113.187.0/26 dev eth1 proto kernel scope link src 195.113.187.37
195.113.233.0/24 dev eth0 proto kernel scope link src 195.113.233.254
192.168.1.0/24 dev eth0 proto kernel scope link src 192.168.1.1
default via 195.113.233.1 dev eth0
```

```
chlivek:~# route -n
Kernel IP routing table
Destination     Gateway         Genmask        Flags Metric Ref  Use
Iface
195.113.187.33 0.0.0.0      255.255.255.255 UH   0     0     0
venet0
192.168.1.2    0.0.0.0      255.255.255.255 UH   0     0     0
venet0
195.113.233.253 0.0.0.0    255.255.255.255 UH   0     0     0
venet0
195.113.233.252 0.0.0.0    255.255.255.255 UH   0     0     0
venet0
195.113.187.0  0.0.0.0      255.255.255.192 U    0     0     0 eth1
195.113.233.0  0.0.0.0      255.255.255.0   U    0     0     0 eth0
192.168.1.0    0.0.0.0      255.255.255.0   U    0     0     0 eth0
0.0.0.0        195.113.233.1 0.0.0.0      UG   0     0     0 eth0
```

Pinging from system 195.113.187.33 outside:

```
ermon:~# ping -c 1 195.113.233.254 (HW node)
PING 195.113.233.254 (195.113.233.254) 56(84) bytes of data.
64 bytes from 195.113.233.254: icmp_seq=1 ttl=64 time=0.035 ms
```

```
ermon:~# ping -c 1 195.113.233.1 (Gateway)
PING 195.113.233.1 (195.113.233.1) 56(84) bytes of data.
64 bytes from 195.113.233.1: icmp_seq=1 ttl=254 time=0.472 ms
```

```
ermon:~# ping -c 1 195.113.233.253 (VE using eth0)
PING 195.113.233.253 (195.113.233.253) 56(84) bytes of data.
```

From 192.168.1.1 icmp_seq=1 Time to live exceeded

I'm bit curious where that 192.168.1.1 get into path. In FW rules I'm using:

```
iptables -t nat -A POSTROUTING -s 192.168.1.0/24 -o eth0 -j MASQUERADE  
echo 1 > /proc/sys/net/ipv4/ip_forward
```

for translating 192.168.1.0/24 onto public 195.113.233.254.

I used http://wiki.openvz.org/Source_based_routing as base for setup,
but I'm really clueless how to fix it. Please can someone review this
setup and suggest me better way how to setup this?

Best regards

--

Jan Tomasek aka Semik
<http://www.tomasek.cz/>
