
Subject: Re: gentoo baselayout 1.13 openvz modifications
Posted by [Roy Marples](#) on Fri, 26 Jan 2007 16:02:15 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Mon, 22 Jan 2007 17:58:05 +0300

Kir Kolyshkin <kir@openvz.org> wrote:

> I was checking the stuff added to Gentoo's baselayout 1.13 to make it
> compatible with VPS systems like Linux-VServer or OpenVZ.

>

> Everything looks great, the only minor problem I found is this code
> in bootmisc:

>

```
>     if [[ $(uname) == "Linux" ]] && ! is_vps_sys ; then  
>         # BSD has it's own sysctl init script  
>         if [[ -e /etc/sysctl.conf ]] ; then  
>             ebegin $"Configuring kernel parameters"  
>             sysctl -q -p /etc/sysctl.conf  
>             eend $?  
>         fi  
>     fi
```

>

> The problem here is in OpenVZ some of sysctl variables are
> virtualized, i.e. you can set it from inside your VE. Usually this is
> not needed, and not too many people do that, but still if there
> is /etc/sysctl.conf people expect that it will be applied during VE
> start.

Hollow asked for that for a reason. I'll assume that he's on the
vserver-devs@gentoo.org mailing list and he'll tell me why.

Otherwise I have no problem with punting it myself.

Thanks

Roy
