

---

Subject: [PATCH -mm] sn2: use static ->proc\_fops  
Posted by [adobriyan](#) on Mon, 29 Jan 2007 12:23:12 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

fix-rmmod-read-write-races-in-proc-entries.patch doesn't want dynamically allocated ->proc\_fops, because it will set it to NULL at module unload time.

Regardless of module status, switch to statically allocated ->proc\_fops which leads to simpler code without wrappers.

AFAICS, also fix the following bug: "sn\_force\_interrupt" proc entry set ->write for itself, but was created with 0444 permissions. Change to 0644.

Signed-off-by: Alexey Dobriyan <[adobriyan@openvz.org](mailto:adobriyan@openvz.org)>

---

```
arch/ia64/sn/kernel/sn2/sn_proc_fs.c | 105 ++++++-----  
1 file changed, 62 insertions(+), 43 deletions(-)
```

```
--- a/arch/ia64/sn/kernel/sn2/sn_proc_fs.c  
+++ b/arch/ia64/sn/kernel/sn2/sn_proc_fs.c  
@@ -89,61 +89,80 @@ static int coherence_id_open(struct inode  
    return single_open(file, coherence_id_show, NULL);  
}  
  
-static struct proc_dir_entry  
-*sn_proofs_create_entry(const char *name, struct proc_dir_entry *parent,  
- int (*openfunc)(struct inode *, struct file *),  
- int (*releasefunc)(struct inode *, struct file *),  
- ssize_t (*write) (struct file *, const char __user *, size_t, loff_t *))  
-{  
- struct proc_dir_entry *e = create_proc_entry(name, 0444, parent);  
-  
- if (e) {  
- struct file_operations *f;  
-  
- f = kzalloc(sizeof(*f), GFP_KERNEL);  
- if (f) {  
- f->open = openfunc;  
- f->read = seq_read;  
- f->llseek = seq_llseek;  
- f->release = releasefunc;  
- f->write = write;  
- e->proc_fops = f;  
- }  
- }  
-  
- return e;
```

```

-}

/*
 * /proc/sgi_sn/sn_topology uses seq_file, see sn_hwperf.c */
extern int sn_topology_open(struct inode *, struct file *);
extern int sn_topology_release(struct inode *, struct file *);

+static const struct file_operations proc_partition_id_fops = {
+ .open = partition_id_open,
+ .read = seq_read,
+ .llseek = seq_llseek,
+ .release = single_release,
+};
+
+static const struct file_operations proc_system_sn_fops = {
+ .open = system_serial_number_open,
+ .read = seq_read,
+ .llseek = seq_llseek,
+ .release = single_release,
+};
+
+static const struct file_operations proc_license_id_fops = {
+ .open = licenseID_open,
+ .read = seq_read,
+ .llseek = seq_llseek,
+ .release = single_release,
+};
+
+static const struct file_operations proc_sn_force_intr_fops = {
+ .open = sn_force_interrupt_open,
+ .read = seq_read,
+ .write = sn_force_interrupt_write_proc,
+ .llseek = seq_llseek,
+ .release = single_release,
+};
+
+static const struct file_operations proc_coherence_id_fops = {
+ .open = coherence_id_open,
+ .read = seq_read,
+ .llseek = seq_llseek,
+ .release = single_release,
+};
+
+static const struct file_operations proc_sn_topo_fops = {
+ .open = sn_topology_open,
+ .read = seq_read,
+ .llseek = seq_llseek,
+ .release = sn_topology_release,
+};

```

```

+
void register_sn_procfs(void)
{
    static struct proc_dir_entry *sgi_proc_dir = NULL;
+ struct proc_dir_entry *pde;

BUG_ON(sgi_proc_dir != NULL);
if (!(sgi_proc_dir = proc_mkdir("sgi_sn", NULL)))
    return;

- sn_procfs_create_entry("partition_id", sgi_proc_dir,
- partition_id_open, single_release, NULL);
-
- sn_procfs_create_entry("system_serial_number", sgi_proc_dir,
- system_serial_number_open, single_release, NULL);
-
- sn_procfs_create_entry("licenseID", sgi_proc_dir,
- licenseID_open, single_release, NULL);
-
- sn_procfs_create_entry("sn_force_interrupt", sgi_proc_dir,
- sn_force_interrupt_open, single_release,
- sn_force_interrupt_write_proc);
-
- sn_procfs_create_entry("coherence_id", sgi_proc_dir,
- coherence_id_open, single_release, NULL);
-
- sn_procfs_create_entry("sn_topology", sgi_proc_dir,
- sn_topology_open, sn_topology_release, NULL);
+ pde = create_proc_entry("partition_id", 0444, sgi_proc_dir);
+ if (pde)
+ pde->proc_fops = &proc_partition_id_fops;
+ pde = create_proc_entry("system_serial_number", 0444, sgi_proc_dir);
+ if (pde)
+ pde->proc_fops = &proc_system_sn_fops;
+ pde = create_proc_entry("licenseID", 0444, sgi_proc_dir);
+ if (pde)
+ pde->proc_fops = &proc_license_id_fops;
+ pde = create_proc_entry("sn_force_interrupt", 0644, sgi_proc_dir);
+ if (pde)
+ pde->proc_fops = &proc_sn_force_intr_fops;
+ pde = create_proc_entry("coherence_id", 0444, sgi_proc_dir);
+ if (pde)
+ pde->proc_fops = &proc_coherence_id_fops;
+ pde = create_proc_entry("sn_topology", 0444, sgi_proc_dir);
+ if (pde)
+ pde->proc_fops = &proc_sn_topo_fops;
}

```

```
#endif /* CONFIG_PROC_FS */
```

---