
Subject: [PATCH 1/7] SUNRPC: create RPC pipefs superblock per network namespace context

Posted by [Stanislav Kinsbursky](#) on Fri, 28 Oct 2011 14:25:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

This is the initial step of RPC pipefs virtualization. It changes nothing to current pipefs behaviour except that mount of pipefs in other than init_net network namespace context will provide only root tree. No other dentries will be visible.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

```
net/sunrpc/rpc_pipe.c | 3 +-  
1 files changed, 2 insertions(+), 1 deletions(-)
```

```
diff --git a/net/sunrpc/rpc_pipe.c b/net/sunrpc/rpc_pipe.c
```

```
index b181e34..ad517bd 100644
```

```
--- a/net/sunrpc/rpc_pipe.c
```

```
+++ b/net/sunrpc/rpc_pipe.c
```

```
@@ -1006,6 +1006,7 @@ rpc_fill_super(struct super_block *sb, void *data, int silent)
```

```
{  
    struct inode *inode;  
    struct dentry *root;
```

```
+ struct net *net = data;
```

```
    sb->s_blocksize = PAGE_CACHE_SIZE;  
    sb->s_blocksize_bits = PAGE_CACHE_SHIFT;
```

```
@@ -1030,7 +1031,7 @@ static struct dentry *
```

```
rpc_mount(struct file_system_type *fs_type,  
           int flags, const char *dev_name, void *data)
```

```
{  
- return mount_single(fs_type, flags, data, rpc_fill_super);
```

```
+ return mount_ns(fs_type, flags, current->nsproxy->net_ns, rpc_fill_super);
```

```
}
```

```
static struct file_system_type rpc_pipe_fs_type = {
```
