# Subject: Service restart on host system kills same service inside all VEs Posted by antoney on Fri, 11 Nov 2011 12:53:34 GMT

View Forum Message <> Reply to Message

Hello, guys.

Everything is in subject. I'm experiencing this problem on both my openvz hosts. For httpd it happens from time to time, for nrpe - always...
Tell please where should I look.

In /proc/user\_beancounters "failcnt" is 0 for all options.

Anton

Subject: Re: Service restart on host system kills same service insideall VEs Posted by Stoyan Stoyanov on Fri, 11 Nov 2011 13:20:10 GMT View Forum Message <> Reply to Message

Hi man,

I was used nrpe inside vz containers and on the hn from along time ago and never see behavior like this. Is there some customizations in your nrpe service start/stop scripts or something, I think there is the place too look at why this happens. ... I think this situation is not openvz related in specific, correct me if im wrong

best regs

On Nov 11, 2011, at 2:53 PM, Anton Zaytsev wrote:

- > Hello, guys.
- >
- > Everything is in subject. I'm experiencing this problem on both my
- > openvz hosts. For httpd it happens from time to time, for nrpe -
- > always...
- > Tell please where should I look.
- > In /proc/user\_beancounters "failcnt" is 0 for all options.
- > Anton
- > Anion
- >
- > <ATT00001.txt>

Stoyan Stoyanov Core System Administrator

#### CONFIDENTIAL

The information contained in this email and any attachment is confidential. It is intended only for the named addressee(s). If you are not the named addressee(s) please notify the sender immediately and do not disclose, copy or distribute the contents to any other person other than the intended addressee(s).

## File Attachments

1) maxtelecom-logo.gif, downloaded 455 times

Subject: Re: Service restart on host system kills same service inside all VEs Posted by Gary Wallis on Fri, 11 Nov 2011 13:31:36 GMT

View Forum Message <> Reply to Message

Anton Zaytsev wrote:

> Hello, guys.

>

- > Everything is in subject. I'm experiencing this problem on both my
- > openvz hosts. For httpd it happens from time to time, for nrpe always...
- > Tell please where should I look.
- > In /proc/user\_beancounters "failcnt" is 0 for all options.

>

Your service restart script X (/etc/init.d/X) is probably killing processes it should not.

E.g. host system kill will kill processes "inside" the containers.

Cheers,

Gary

Subject: Re: Service restart on host system kills same service insideall VEs Posted by antoney on Fri, 11 Nov 2011 13:40:58 GMT

View Forum Message <> Reply to Message

Thanks for quick reply.

- > Is there some customizations in your nrpe service start/stop scripts or
- > something

no, all scripts are default. This happens for httpd too.

I suppose it's openvz related. Seems like some misunderstanding between host and ve...

Systems are centos 4 and 5, latest kernels from repo.

On Fri, Nov 11, 2011 at 3:20 PM, Stoyan Stoyanov <s.stoianov@maxtelecom.bg>wrote:

```
> Hi man,
>
> I was used nrpe inside vz containers and on the hn from along time ago and
> never see behavior like this. Is there some customizations in your nrpe
> service start/stop scripts or something, I think there is the place too
> look at why this happens. ... I think this situation is not openvz related
> in specific, correct me if im wrong
> best regs
>
>
>
>
> On Nov 11, 2011, at 2:53 PM, Anton Zaytsev wrote:
> Hello, guys.
>> Everything is in subject. I'm experiencing this problem on both my openvz
>> hosts. For httpd it happens from time to time, for nrpe - always...
>> Tell please where should I look.
>> In /proc/user beancounters "failcnt" is 0 for all options.
>>
>> Anton
>>
>> <ATT00001.txt>
>
> Stovan Stovanov
> Core System Administrator
>
>
>
>
> CONFIDENTIAL
> The information contained in this email and any attachment is
> confidential. It is intended only for the named addressee(s). If you are
> not the named addressee(s) please notify the sender immediately and do not
> disclose, copy or distribute the contents to any other person other than
> the intended addressee(s).
>
```

# Subject: Re: Service restart on host system kills same serviceinsideall VEs Posted by Stoyan Stoyanov on Fri, 11 Nov 2011 13:52:10 GMT

View Forum Message <> Reply to Message

Like Gary says, the host system just kills the ct's proceses (may be in a killall `procesname` style :))) so the thing that u should take care is the proces's start/stop scripts

On Nov 11, 2011, at 3:40 PM, Anton Zaytsev wrote:

```
> Thanks for quick reply.
>
> Is there some customizations in your nrpe service start/stop scripts
> or something
> no, all scripts are default. This happens for httpd too.
> I suppose it's openvz related. Seems like some misunderstanding
> between host and ve...
> Systems are centos 4 and 5, latest kernels from repo.
> On Fri, Nov 11, 2011 at 3:20 PM, Stoyan Stoyanov <s.stoianov@maxtelecom.bg
> > wrote:
> Hi man,
>
> I was used nrpe inside vz containers and on the hn from along time
> ago and never see behavior like this. Is there some customizations
> in your nrpe service start/stop scripts or something. I think there
> is the place too look at why this happens. ... I think this
> situation is not openvz related in specific, correct me if im wrong
>
> best regs
>
>
>
> On Nov 11, 2011, at 2:53 PM, Anton Zaytsev wrote:
> Hello, guys.
> Everything is in subject. I'm experiencing this problem on both my
> openvz hosts. For httpd it happens from time to time, for nrpe -
> always...
> Tell please where should I look.
> In /proc/user_beancounters "failcnt" is 0 for all options.
```

#### CONFIDENTIAL

Stoyan Stoyanov

Core System Administrator

The information contained in this email and any attachment is confidential. It is intended only for the named addressee(s). If you are not the named addressee(s) please notify the sender immediately and do not disclose, copy or distribute the contents to any other person other than the intended addressee(s).

#### File Attachments

1) maxtelecom-logo.gif, downloaded 482 times

Subject: Re: Service restart on host system kills same service insideall VEs Posted by antoney on Fri, 11 Nov 2011 14:04:25 GMT View Forum Message <> Reply to Message

Ok, nrpe init script does "killproc nrpe" and its killing all processes named nrpe, inside containers too. But almost all of init scripts do so. So modify all of them? Looks not so pretty:)

On Fri, Nov 11, 2011 at 3:40 PM, Anton Zaytsev <anton.zajtsev@gmail.com>wrote:

```
> Thanks for quick reply.
>
>> Is there some customizations in your nrpe service start/stop scripts or
>> something
> no, all scripts are default. This happens for httpd too.
> I suppose it's openvz related. Seems like some misunderstanding between
> host and ve...
> Systems are centos 4 and 5, latest kernels from repo.
> On Fri, Nov 11, 2011 at 3:20 PM, Stoyan Stoyanov <s.stoianov@maxtelecom.bg
> > wrote:
>> Hi man,
>>
>> I was used nrpe inside vz containers and on the hn from along time ago
>> and never see behavior like this. Is there some customizations in your nrpe
>> service start/stop scripts or something, I think there is the place too
>> look at why this happens. ... I think this situation is not openvz related
>> in specific, correct me if im wrong
>>
>> best regs
>>
>>
>>
>>
>> On Nov 11, 2011, at 2:53 PM, Anton Zaytsev wrote:
>> Hello, guys.
>>> Everything is in subject. I'm experiencing this problem on both my
>>> openvz hosts. For httpd it happens from time to time, for nrpe - always...
>>> Tell please where should I look.
>>> In /proc/user_beancounters "failcnt" is 0 for all options.
>>>
>>> Anton
>>>
>>> <ATT00001.txt>
>>>
>>
>> Stoyan Stoyanov
>> Core System Administrator
>>
>>
>>
```

```
>> CONFIDENTIAL
>> The information contained in this email and any attachment is
>> confidential. It is intended only for the named addressee(s). If you are
>> not the named addressee(s) please notify the sender immediately and do not
>> disclose, copy or distribute the contents to any other person other than
>> the intended addressee(s).
>>
>>
```

# Subject: Re: Service restart on host system kills same serviceinsideall VEs Posted by Stoyan Stoyanov on Fri, 11 Nov 2011 14:46:45 GMT

View Forum Message <> Reply to Message

Agree :) it's not so pretty.. but every process from every container is a seen process on the host

On Nov 11, 2011, at 4:04 PM, Anton Zaytsev wrote:

```
> Ok, nrpe init script does "killproc nrpe" and its killing all
> processes named nrpe, inside containers too. But almost all of init
> scripts do so.
> So modify all of them? Looks not so pretty:)
> On Fri, Nov 11, 2011 at 3:40 PM, Anton Zaytsev <anton.zajtsev@gmail.com
> > wrote:
> Thanks for quick reply.
>
> Is there some customizations in your nrpe service start/stop scripts
> or something
> no, all scripts are default. This happens for httpd too.
> I suppose it's openvz related. Seems like some misunderstanding
> between host and ve...
> Systems are centos 4 and 5, latest kernels from repo.
> On Fri, Nov 11, 2011 at 3:20 PM, Stoyan Stoyanov <s.stoianov@maxtelecom.bg
> > wrote:
> Hi man,
> I was used nrpe inside vz containers and on the hn from along time
> ago and never see behavior like this. Is there some customizations
> in your nrpe service start/stop scripts or something, I think there
> is the place too look at why this happens. ... I think this
```

>

> situation is not openvz related in specific, correct me if im wrong

```
> best regs
>
>
>
> On Nov 11, 2011, at 2:53 PM, Anton Zaytsev wrote:
> Hello, guys.
>
> Everything is in subject. I'm experiencing this problem on both my
> openvz hosts. For httpd it happens from time to time, for nrpe -
> always...
> Tell please where should I look.
> In /proc/user_beancounters "failcnt" is 0 for all options.
>
> Anton
> <ATT00001.txt>
> Stoyan Stoyanov
> Core System Administrator
>
>
>
> CONFIDENTIAL
> The information contained in this email and any attachment is
> confidential. It is intended only for the named addressee(s). If you
> are not the named addressee(s) please notify the sender immediately
> and do not disclose, copy or distribute the contents to any other
> person other than the intended addressee(s).
>
> <ATT00001.txt>
Stoyan Stoyanov
```

#### CONFIDENTIAL

Core System Administrator

The information contained in this email and any attachment is confidential. It is intended only for the named addressee(s). If you are not the named addressee(s) please notify the sender immediately and do not disclose, copy or distribute the contents to any other

person other than the intended addressee(s).

### File Attachments

1) maxtelecom-logo.gif, downloaded 499 times

Subject: Re: Service restart on host system kills same service insideall VEs Posted by Tim Small on Fri, 11 Nov 2011 15:37:15 GMT

View Forum Message <> Reply to Message

On 11/11/11 14:04, Anton Zaytsev wrote:

- > Ok, nrpe init script does "killproc nrpe" and its killing all processes
- > named nrpe, inside containers too. But almost all of init scripts do so.
- > So modify all of them? Looks not so pretty:)

>

Use Debian? I've not seen this broken behaviour with any of Debian's init scripts...

I would say that it's also broken for non-openvz hosts - I've previously run several separate copies of apache and ssh (each with their own init scripts) on a Debian host before, and restarting one hasn't killed the others...

Open bugs against Redhat/CentOS? I'd guess this problem will continue with LXC in the future too...

Tim.

--

South East Open Source Solutions Limited

Registered in England and Wales with company number 06134732.

Registered Office: 2 Powell Gardens, Redhill, Surrey, RH1 1TQ

VAT number: 900 6633 53 http://seoss.co.uk/ +44-(0)1273-808309

Subject: Re: Service restart on host system kills same serviceinsideall VEs Posted by antoney on Fri, 11 Nov 2011 15:59:26 GMT

View Forum Message <> Reply to Message

Ok, I've decided to just leave it as is. It's production systems, service restarts are not so often.

So only solution for this issue now is to use host system just as host.

Tim,

Migration to Debian will be not so simple.

Yes, I think it's needed to send bug report to CentOS/Redhat packaging. I

surprised that no one has mentioned this before.

On Fri, Nov 11, 2011 at 4:46 PM, Stoyan Stoyanov

```
<s.stoianov@maxtelecom.bg>wrote:
> Agree :) it's not so pretty.. but every process from every container is a
> seen process on the host
>
> On Nov 11, 2011, at 4:04 PM, Anton Zaytsev wrote:
>
> Ok, nrpe init script does "killproc nrpe" and its killing all processes
>> named nrpe, inside containers too. But almost all of init scripts do so.
>> So modify all of them? Looks not so pretty:)
>>
>> On Fri, Nov 11, 2011 at 3:40 PM, Anton Zaytsev <anton.zajtsev@gmail.com>
>> wrote:
>> Thanks for quick reply.
>> Is there some customizations in your nrpe service start/stop scripts or
>> something
>> no, all scripts are default. This happens for httpd too.
>> I suppose it's openvz related. Seems like some misunderstanding between
>> host and ve...
>> Systems are centos 4 and 5, latest kernels from repo.
>>
>> On Fri, Nov 11, 2011 at 3:20 PM, Stoyan Stoyanov <
>> s.stoianov@maxtelecom.bg> wrote:
>> Hi man.
>>
>> I was used nrpe inside vz containers and on the hn from along time ago
>> and never see behavior like this. Is there some customizations in your nrpe
>> service start/stop scripts or something, I think there is the place too
>> look at why this happens. ... I think this situation is not openvz related
>> in specific, correct me if im wrong
>>
>> best regs
>>
>>
>>
>>
>>
>> On Nov 11, 2011, at 2:53 PM, Anton Zaytsev wrote:
>>
>> Hello, guys.
>>
>> Everything is in subject. I'm experiencing this problem on both my openvz
```

```
>> hosts. For httpd it happens from time to time, for nrpe - always...
>> Tell please where should I look.
>> In /proc/user_beancounters "failcnt" is 0 for all options.
>> Anton
>>
>> <ATT00001.txt>
>>
>> Stoyan Stoyanov
>> Core System Administrator
>>
>>
>>
>>
>> CONFIDENTIAL
>> The information contained in this email and any attachment is
>> confidential. It is intended only for the named addressee(s). If you are
>> not the named addressee(s) please notify the sender immediately and do not
>> disclose, copy or distribute the contents to any other person other than
>> the intended addressee(s).
>>
>>
>>
>>
>> Users mailing list
>> Users@openvz.org
>> https://openvz.org/mailman/**listinfo/users<https://openvz.org/mailman/listinfo/users>
>>
>>
>> <ATT00001.txt>
>>
> Stoyan Stoyanov
> Core System Administrator
>
>
>
> CONFIDENTIAL
> The information contained in this email and any attachment is
> confidential. It is intended only for the named addressee(s). If you are
> not the named addressee(s) please notify the sender immediately and do not
> disclose, copy or distribute the contents to any other person other than
> the intended addressee(s).
>
```

# Subject: Re: Service restart on host system kills same serviceinsideall VEs Posted by antoney on Fri, 11 Nov 2011 16:42:53 GMT

View Forum Message <> Reply to Message

```
>
> Yes, I think it's needed to send bug report to CentOS/Redhat packaging. I
> surprised that no one has mentioned this before.
I mean this bug)
On Fri, Nov 11, 2011 at 5:59 PM, Anton Zaytsev <anton.zajtsev@gmail.com>wrote:
> Ok, I've decided to just leave it as is. It's production systems, service
> restarts are not so often.
> So only solution for this issue now is to use host system just as host.
>
> Tim,
> Migration to Debian will be not so simple.
> Yes, I think it's needed to send bug report to CentOS/Redhat packaging. I
> surprised that no one has mentioned this before.
> On Fri, Nov 11, 2011 at 4:46 PM, Stoyan Stoyanov <s.stoianov@maxtelecom.bg
> > wrote:
>> Agree :) it's not so pretty.. but every process from every container is a
>> seen process on the host
>>
>>
>> On Nov 11, 2011, at 4:04 PM, Anton Zaytsev wrote:
>> Ok, nrpe init script does "killproc nrpe" and its killing all processes
>>> named nrpe, inside containers too. But almost all of init scripts do so.
>>> So modify all of them? Looks not so pretty:)
>>>
>>> On Fri, Nov 11, 2011 at 3:40 PM, Anton Zaytsev <anton.zajtsev@gmail.com>
>>> wrote:
>>> Thanks for quick reply.
>>>
>>> Is there some customizations in your nrpe service start/stop scripts or
>>> something
>>> no, all scripts are default. This happens for httpd too.
>>> I suppose it's openvz related. Seems like some misunderstanding between
>>> host and ve...
>>> Systems are centos 4 and 5, latest kernels from repo.
>>>
>>> On Fri, Nov 11, 2011 at 3:20 PM, Stoyan Stoyanov <
>>> s.stoianov@maxtelecom.bg> wrote:
>>> Hi man,
```

```
>>>
>>> I was used nrpe inside vz containers and on the hn from along time ago
>>> and never see behavior like this. Is there some customizations in your nrpe
>>> service start/stop scripts or something, I think there is the place too
>>> look at why this happens. ... I think this situation is not openvz related
>>> in specific, correct me if im wrong
>>>
>>> best regs
>>>
>>>
>>>
>>>
>>>
>>> On Nov 11, 2011, at 2:53 PM, Anton Zaytsev wrote:
>>> Hello, guys.
>>>
>>> Everything is in subject. I'm experiencing this problem on both my
>>> openvz hosts. For httpd it happens from time to time, for nrpe - always...
>>> Tell please where should I look.
>>> In /proc/user_beancounters "failcnt" is 0 for all options.
>>>
>>> Anton
>>>
>>> <ATT00001.txt>
>>>
>>> Stoyan Stoyanov
>>> Core System Administrator
>>>
>>>
>>>
>>>
>>> CONFIDENTIAL
>>> The information contained in this email and any attachment is
>>> confidential. It is intended only for the named addressee(s). If you are
>>> not the named addressee(s) please notify the sender immediately and do not
>>> disclose, copy or distribute the contents to any other person other than
>>> the intended addressee(s).
>>>
>>>
>>>
>>> Users mailing list
>>> Users@openvz.org
>>> https://openvz.org/mailman/**listinfo/users<https://openvz.org/mailman/listinfo/users>
>>>
>>>
>>>
```

```
>>> <ATT00001.txt>
>>>
>>
>> Stoyan Stoyanov
>> Core System Administrator
>>
>>
>>
>>
>> CONFIDENTIAL
>> The information contained in this email and any attachment is
>> confidential. It is intended only for the named addressee(s). If you are
>> not the named addressee(s) please notify the sender immediately and do not
>> disclose, copy or distribute the contents to any other person other than
>> the intended addressee(s).
>>
>>
```

Subject: Re: Service restart on host system kills same service insideall VEs Posted by MailingListe on Fri, 11 Nov 2011 20:42:38 GMT

View Forum Message <> Reply to Message

Zitat von Anton Zaytsev <anton.zajtsev@gmail.com>:

- > Ok, nrpe init script does "killproc nrpe" and its killing all processes
- > named nrpe, inside containers too. But almost all of init scripts do so.
- > So modify all of them? Looks not so pretty:)

you should not run any services beside maybe SSH on the hardware node. It is the "root" node and should only be used to manage the VEs. Every problem you got with any service running at the HN will affect all VEs. Use the HN only as hypervisor and you are done.

Regards

**Andreas** 

## File Attachments

1) smime.p7s, downloaded 469 times

Subject: Re: Service restart on host system kills same service insideall VEs Posted by Sharp on Fri, 11 Nov 2011 22:50:24 GMT

View Forum Message <> Reply to Message

On Sat, Nov 12, 2011 at 12:42 AM, < lst hoe02@kwsoft.de> wrote:

- > you should not run any services beside maybe SSH on the hardware node. It is
- > the "root" node and should only be used to manage the VEs.

That's bad advice. It's generally good idea to run things like nrpe and munin on HN to monitor it's performance and status.

SY, Ilya A. Otyutskiy aka Sharp

Subject: Re: Service restart on host system kills same service insideall VEs Posted by MailingListe on Sat, 12 Nov 2011 19:24:23 GMT View Forum Message <> Reply to Message

Zitat von "Ilya A. Otyutskiy" <sharp@thesharp.ru>:

- > On Sat, Nov 12, 2011 at 12:42 AM, < lst\_hoe02@kwsoft.de> wrote:
- >> you should not run any services beside maybe SSH on the hardware node. It is
- >> the "root" node and should only be used to manage the VEs.

- > That's bad advice. It's generally good idea to run things like nrpe
- > and munin on HN to monitor it's performance and status.

If this "things" or the start/stop scripts used tend to kill all kind of processes not belonging to them it \*is\* a really bad idea to run such "things" on the HN. You should only use software absolutely needed and really trustworth at the HN. Do all other things in the VE. This even apply monitor software.

If you do not agree, do not complain about the problems arise.

Regards

**Andreas** 

### File Attachments

1) smime.p7s, downloaded 465 times

Subject: Re: Service restart on host system kills same service insideall VEs Posted by Sharp on Sun, 13 Nov 2011 10:50:42 GMT

View Forum Message <> Reply to Message

On Sat, Nov 12, 2011 at 11:24 PM, < lst hoe02@kwsoft.de> wrote:

- > If this "things" or the start/stop scripts used tend to kill all kind of
- > processes not belonging to them it \*is\* a really bad idea to run such
- > "things" on the HN.

So you are suggesting to throw those useful "things" away instead of patching their init-scripts and sending them to upstream?

- > You should only use software absolutely needed and
- > really trustworth at the HN. Do all other things in the VE. This even apply
- > monitor software.

Maybe you will tell us how to monitor something like HN's disk space from VE? :)

--

SY, Ilya A. Otyutskiy aka Sharp

Subject: Re: Service restart on host system kills same serviceinsideall VEs Posted by Aleksandar Ivanisevic on Mon, 14 Nov 2011 09:57:55 GMT View Forum Message <> Reply to Message

Anton Zaytsev <anton.zajtsev@gmail.com> writes:

- > Ok, I've decided to just leave it as is. It's production systems, service
- > restarts are not so often.
- > So only solution for this issue now is to use host system just as host.

>

- > Tim,
- > Migration to Debian will be not so simple.
- > Yes, I think it's needed to send bug report to CentOS/Redhat packaging. I
- > surprised that no one has mentioned this before.

[...]

It gets mentioned every once in a while, but this is a general problem with centos init scripts and/or most init scripts in general, they are mostly written to assume a single instance of the service.

The solution is simply to run as little as possible on the host, and to fix the scripts for the stuff you need to run. Painful, but unavoidable. Maybe if you submit a patch to rhel, it could maybe make it into a release in a couple of years;)

--

Ti si arogantan, prepotentan i peglaš vlastitu frustraciju. -- Ivan Tišljar, hr.comp.os.linux

Subject: Re: Service restart on host system kills same serviceinsideall VEs

# Posted by antoney on Mon, 14 Nov 2011 16:46:54 GMT

View Forum Message <> Reply to Message

I've submited the bug to RHEL. https://bugzilla.redhat.com/show\_bug.cgi?id=753834

Yes for now it's only to limit services on the host.

On Mon, Nov 14, 2011 at 11:57 AM, Aleksandar Ivanisevic < aleksandar@ivanisevic.de> wrote:

```
> Anton Zaytsev <anton.zajtsev@gmail.com>
> writes:
> > Ok, I've decided to just leave it as is. It's production systems, service
> > restarts are not so often.
>> So only solution for this issue now is to use host system just as host.
> > Tim,
> > Migration to Debian will be not so simple.
> Yes, I think it's needed to send bug report to CentOS/Redhat packaging. I
> > surprised that no one has mentioned this before.
>
> [...]
>
> It gets mentioned every once in a while, but this is a general problem
> with centos init scripts and/or most init scripts in general, they are
> mostly written to assume a single instance of the service.
> The solution is simply to run as little as possible on the host, and
> to fix the scripts for the stuff you need to run. Painful, but
> unavoidable. Maybe if you submit a patch to rhel, it could maybe make
> it into a release in a couple of years;)
>
>
> Ti si arogantan, prepotentan i peglaš vlastitu frustraciju. -- Ivan
> Tišljar, hr.comp.os.linux
```

Subject: Re: Service restart on host system kills same serviceinsideall VEs Posted by Tim Small on Mon, 14 Nov 2011 17:56:35 GMT

View Forum Message <> Reply to Message

On 14/11/11 16:46, Anton Zaytsev wrote:

- > I've submited the bug to RHEL.
- > https://bugzilla.redhat.com/show\_bug.cgi?id=753834

> Yes for now it's only to limit services on the host.

>

To get this bug taken more seriously, I would be more concrete.

e.g. give the name of an init script which fails, and corresponding rpm which it shipped with.

Give the example of a development server which runs multiple copies of said service for multiple developers (with separate config/data/pid files). Say that restarting the system service kills all copies.

paste in some shell history exhibiting this behaviour.

I'd also mention that Debian, Ubuntu etc. doesn't exhibit this behaviour e.g. search for "and that they don't kill unfortunately-named user processes" in http://www.debian.org/doc/debian-policy/ch-opersys.html

Cheers,

Tim.

--

South East Open Source Solutions Limited Registered in England and Wales with company number 06134732. Registered Office: 2 Powell Gardens, Redhill, Surrey, RH1 1TQ VAT number: 900 6633 53 http://seoss.co.uk/ +44-(0)1273-808309

Subject: Re: Service restart on host system kills same serviceinsideall VEs Posted by Aleksandar Ivanisevic on Tue, 15 Nov 2011 09:43:49 GMT View Forum Message <> Reply to Message

Anton Zaytsev <anton.zajtsev@gmail.com> writes:

- > I've submited the bug to RHEL.
- > https://bugzilla.redhat.com/show\_bug.cgi?id=753834

Eh, you have filed it against EL4, which is going to be EOLed in 3 months;)